

OverGate swing gate, single unit with motorized drive, column right or left



The Gunnebo OverGate is a unidirectional motorized swing gate originally developed for access control and customer guidance in retail stores. It is also a valuable and cost effective entrance solution that exists in security installations alongside turnstiles or other products. It is available in right, left or double configurations with standard arm length. The OverGate is manufactured from 304 polished stainless steel (only available in the OverGate C0 version) and has the same Gunnebo finish as the Gunnebo turnstile, making it a perfect match. The OverGate entrance gate is equipped with an anti-panic device: When an appropriate force (approximately over 110N) is exceeded, the swing gate disengages to create a clear exit in both directions. The OverGate Entrance Gate also has a push button control to operate the unit and is fitted as standard with white signage with an arrow on the opening side and a 'No Entry' sign on the opposite side. Other signage options are also available. The system opens and closes at adjustable intervals from 0 to 15 seconds.

- in polished stainless steel
- with locking bar, adjustable length 700-1100 mm
- Overall width: 900-1300 mm
- Clear passage width: 650-1050 mm
- Sash locking height OKFF: 926 mm
- Column height OKFF: 1140 mm
- Motorized pillar made of 1.5 mm stainless steel sheet
- Opening angle: 90°
- Hold-open time: adjustable between 0 and 15 seconds
- Operating voltage: 100-240V 50/60 Hz
- Input power: 800 W
- Weight: approx. 31 kg
- Complies with UNI EN 1125

item number	WL45458
model	Einzelanlage mit Motorantrieb, Säule RECHTS
manufacturer	GUNNEBO
manufacturer item number	232995010-230283100
GPSR manufacturer information	Gunnebo Entrance Control GmbH Carl-Zeiss-Str. 8 DE-85748 Garching www.gunneboentrancecontrol.com
order unit	1 piece
content unit	1 piece