

2 Tool DDE soldering station, with electric pump 230 V, with T245 and DR560



Description

- manages up to 2 handpieces simultaneously
- compatible with 10 JBC handpieces (PA120-A, AM120-A, T210-A, T210-NA, T245-A, T245-NA, HT420-A, DS360-A, DR560-A, AP250-A)
- MSE desoldering module creates the necessary vacuum to remove the molten solder
- Peak power 150 W per tool

Product details

item number	WL45630
manufacturer	JBC
manufacturer item number	DDSE-2QC
model	DDSE-2QC
dimensions with packaging (LxWxH)	368 mm x 474 mm x 195 mm
scope of supply	Double supply unit DDE-2C with standby function Soldering iron T245-A Shelf AD-SE Desoldering iron DR560-A

Products for the electronic industry



	Shelf DR-SE Desoldering pump MSE-A (electric) Cleaning set CL8499 for soldering tips SCH-A tip holder
order unit	piece
product series	premium line
heat-up rating	150 W
voltage	230 V
vacuum	75% / 570 mmHg / 22.4 inHg
temperature range °C	90–450 °C
station type	soldering station
included stand	AD-SE, DR-SE, SCH-A
included control unit	DDE, MSE-A
included handpiece	=== PROUDLY PRESENTS
included cleaning set	CL8499
Tip to ground resistance	<2 Ohm
ambient operating temperature	10–50 °C
capacity	9 SLPM
connections	USB-B, USB-A, robot RS-232, LAN, equipotential bonding: optional connection to EPA