

Complete rework station with pneumatic pump, 230 V



Description

- for soldering and reworking with hot air
- consists of stackable modules and all necessary accessories
- DDE manages up to 2 tools simultaneously
- compatible with 12 JBC handpieces (PA120-A, AM120-A, T210-A, T210-NA, T245-A, T245-NA, HT420-A, DS360-A, DR560-A, AP250-A, JT-TA, TE-TB)
- the pneumatic desoldering module MVE is necessary for a complete desoldering process (clean and dry compressed air necessary)
- JTSE controls rework based on temperature and airflow profiles
- Peak power: 150 W per tool DDE, 700 W JTSE
- DDE: 90 to 450 °C
- JTSE: 150 to 450 °C

Product details

item number	WL45636
manufacturer	JBC
manufacturer item number	RMVE-2QE
model	RMVE-2QE
dimensions with packaging (LxWxH)	370 mm x 480 mm x 380 mm
scope of supply	JTSE hot air station DDE 2 Tool control unit

Products for the electronic industry



	<p>MVE-A Pneumatic desoldering module for DDE & DME T245-A Handpiece (soldering tip not included) DR560-A Desoldering iron JT-TA Heating hose sets SCH-A soldering tip holder AD-SE stand for T210 & T245 handpieces DR-SE Stand for DR560 JT-SE stand for JT heater CL8499 Manual tip cleaner JN2015 Nozzle for JT heater JN2012 Nozzle for JT heater JN2020 Nozzle for JT heater T260-A Pick & Place (assembly) 0008752 Pulling stand PH218 Thermocouple type K</p>
order unit	piece
product series	premium line
heat-up rating	150 W
pressure (to)	6 Bar
voltage	230 V
vacuum	90% / 680 mmHg / 26.8 inHg
station type	desoldering station, soldering station
included stand	AD-SE, DR-SE
included control unit	DDE, MVE-A
included handpiece	---PROUDLY PRESENTS
included cleaning set	CL8499
Tip to ground resistance	<2 Ohm
ambient operating temperature	10–50 °C
capacity	15 SLPM
connections	USB-B, USB-A, Robot RS-232, Thermocouple, Pedal (JTSE), Aux (JTSE), Equipotential bonding