

LED flexible tube light ROCIA.focus, 10° optics, 8 W, 12-40 V



The ROCIA.focus kompakt RFF 600/850/DS LED flexible tube luminaire with 10° optics from Waldmann is a machine luminaire that is extremely resistant and also consists of a robust aluminum housing with a solid safety glass cover. Even in the harshest machine environment, the flexible tube luminaire retains its stability. The flexible tube with additional head joint makes the machine light mobile and brings the light directly and quickly to the point - always exactly where it is needed. Thanks to the flexible tube, the lighting can be precisely aligned even in confined spaces. The dimmable LED machine light is very bright and has an extremely long service life of at least 50,000 hours and low energy consumption. Even when not dimmed, the ROCIA.focus LED flexible tube luminaire saves up to 90% energy compared to corresponding halogen luminaires. It guarantees absolutely even and flicker-free light and has minimal heat development in the direction of radiation.

- maximum illuminance 30,053 lx
- powerful high power LEDs for maximum light
- 10° beam angle

- pinpoint illumination
- precisely adjustable flexible hose
- Metal flexible hose for at least 20 000 movements
- Colour temperature neutral white 5.000 K
- Colour rendering Ra > 80
- maintenance-free LED technology
- LED service life (L70) > 60 000 h
- continuous and flicker-free dimming
- robust housing with solid safety glass cover
- Viton® seal for a high degree of protection
- chemically resistant to many media
- Pushbuttons in the luminaire head for on / off and dimming

item number	WL45698
model	RFF600/850/DS
manufacturer	WALDMANN
manufacturer item number	113184000-00680272
GPSR manufacturer information	WALDMANN Lichttechnik Peter-Henlein-Straße 5 DE-78056 Villingen-Schwenningen www.waldmann.com
order unit	1 piece
content unit	1 piece
material	Aluminium
Lamp or magnifier type	Flexible tube light
connections	12-28 VAC, 12-40 VDC
dimmable	yes
colour temperature	5000 °K
power	8 W
equipping	LED, neutral white
attachment	Table mounting
housing colour	black
protection class	3
protection class	67 IP
ESD safe	no