

Universal stripping tool, 125 mm, sales packaging



Suitable for stripping all common round and wet room cables from Ø 8.0 to 13.0 mm (e.g. NYM cable 3 x 1.5 mm² to 5 x 2.5 mm²). Also for use in junction or distribution boxes. Double-shell, hinged stripping tool. With opening spring and ratchet. Fastening clip for safe storage. Also with longitudinal cutter. Internal knife that can be pushed out. Stripping device for cross-sections 0.2 / 0.3 / 0.8 / 1.5 / 2.5 / 4 mm². with integrated cable guide for longitudinal cutting. Solid insulations (e.g. halogen-free) can be stripped more easily. - Stripping values square millimetres: 0.2 - 4mm² - Stripping values (diameter): Ø 8 - 13mm - Cable type: round cable, e. g.: 3 x 1.5 mm² to 5 x 2.5 mm² Round cable, e.g.: 3 x 1.5 mm² to 5 x 2.5 mm²

- Suitable for stripping all common round and wet room cables from Ø 8.0 to 13.0 mm (e.g. NYM cable 3 x 1.5 mm² to 5 x 2.5 mm²)
- Also for use in junction or distribution boxes
- Double-shell, hinged stripping tool
- With opening spring and ratchet
- Fastening clip for safe storage

item number

WL46167

model

16 85 125 SB

Products for the electronic industry



manufacturer	KNIPEX
manufacturer item number	16 85 125 SB
length	181 mm
width	86 mm
height	36 mm
length with packaging	344 mm
width with packaging	115 mm
height with packaging	92 mm
Packaging volume	3.679 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	blister packaging
RoHS conform	no
VDE	no
cable type	Round cable, for example: 3 x 1.5 mm ² up to 5 x 2.5 mm ²
stripping value diameter	8 - 13 mm
Stripping value of single wires	0.2 / 0.3 / 0.8 / 1.5 / 2.5 / 4 mm
ESD safe	no
strip range square millimeter	0.2 – 4 mm ²
type of pliers	hand stripper