

Torque screwdriver TorqueVario®-S, 0.5-2.0 Nm, 4 mm



• Meets your requirements: Variable adjustable torque covers a wide range of applications

Reduces your costs: Electrostatically dissipative tools protect electronic components from destruction

 \bullet Protects your health: with patented SoftFinish® handle design for hand and muscle-friendly work

• Increases your efficiency: the right torque protects you from material damage and reworking

• Standards: IEC 61340-5-1

• DIN EN ISO 6789

• Application For controlled bolting to electrostatically sensitive components at a specified torque, in combination with a Wiha Torque 4 mm ESD interchangeable blade.

| Alternative item description | 28521200 |
|------------------------------|---------------------|
| item number | WL46576 |
| model | 26462 TorqueVario S |
| manufacturer | WIHA |
| manufacturer item number | 26462 |
| order unit | 1 piece |
| content unit | 1 piece |
| product series | 2852 |

Products for the electronic industry





| external hexagon | 4 |
|---------------------|--------------------|
| Torque Nm | 0,5-2,0 |
| handle length | 131 mm |
| tolerance | 6 % |
| VDE | no |
| type of screw | hexagonal |
| ESD safe | no |
| packaging mass | piece |
| type of screwdriver | torque screwdriver |
| tool length | 131 mm |
| handle diameter | 30 mm |

Products for the electronic industry

