

ESD torque screwdriver 1431, Micro ESD 5.0 - 11.0 Ncm



Torque tool with adjustable torque from 2.0 to 11.0 Ncm (precision $\pm 10\%$). Compact handle/interchangeable blade system for torque-controlled fine screw connections. The Kraftform Micro ESD torque screwdriver is ideal for torque-controlled screwdriving on electrostatically sensitive components. Suitable for holding bits with 4 mm half-moon drive (Wera series 9) and bits with 4 mm HIOS drive (Wera series 21). Tamper-proof. Clearly audible and perceptible disengagement when the set torque is reached. Unlimited manual release torque. Electrical surface resistance $\leq 10^9 \text{ Ohm}$ for reliable protection against electrostatic energy. Manufactured in accordance with DIN EN 61340-5-1. Handle/interchangeable blade system for lightning-fast blade replacement. Kraftform Micro handle with rotating cap and quick-twist zone for lightning-fast twirling, no more time-consuming regripping necessary. Power zone with integrated soft zones for transferring high loosening and tightening torques. Precision zone directly above the blade for the correct angle of rotation for adjustment work. Lightning-fast bit fixing: simply push the bit into the holder, automatic locking, secure fit. To change the bit, simply push the sleeve forwards and remove the bit. Free-running actuating sleeve for easy guidance of the tool during the screwdriving process. Bits suitable for manual and machine-operated screwdriving with electric screwdrivers (e.g. HIOS, Delvo, Sehan). Use e.g. on smartphones, cell phones, cameras, electronic devices, in dental laboratories and dental practices.

- Adjustable Kraftform torque screwdriver with quick-change chuck
- Electrostatic safe tool due to surface resistance of $< 10^9 \text{ Ohm}$
- Clearly audible and perceptible over-engagement when the set torque is reached
- Suitable for bits with 4 mm half-moon and 4 mm HIOS drive
- Use e.g. on smartphones, cell phones, cameras and electronic devices

Item no.	WL46880
Model	1430 ESD Kraftform Micro
Manufacturer	WERA
Manufacturer article no.	05074804001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25

DE-42349 Wuppertal-Cronenberg
www.wera.de

Length	145 mm
Width	23 mm
Height	23 mm
Length with packaging	145 mm
Width with packaging	23 mm
Height with packaging	23 mm
Sales unit	1 piece
Content unit	1 piece
VDE	no
ESD compliant	yes
Packaging dimensions	piece
Screwdriver type	torque screwdriver
Torque (from)	0.05 Nm
Torque (to)	0.11 Nm
Tool length	145 mm