

## Sintro table frame, 1830x750x740 mm



The Karl table frame is characterized by its stable construction and high load-bearing capacity.

- Height adjustment with clamping screws
- Sturdy steel construction
- Height adjustment from 740 - 1040 mm
- Height adjustment elements in the foot section
- work surface with 200 kg uniform surface load capacity

|                          |           |
|--------------------------|-----------|
| item number              | WL46942   |
| model                    | 25.045.70 |
| model line               | Sintro    |
| manufacturer             | KARL      |
| manufacturer item number | 25.045.70 |

Products for the electronic industry



|                               |                                                                                       |
|-------------------------------|---------------------------------------------------------------------------------------|
| GPSR manufacturer information | Andreas KARL GmbH & Co. KG<br>Hauptstraße 26<br>DE-85777 Fahrenzhausen<br>www.karl.eu |
| width                         | 1830 mm                                                                               |
| height                        | 740 mm                                                                                |
| depth                         | 750 mm                                                                                |
| order unit                    | 1 piece                                                                               |
| content unit                  | 1 piece                                                                               |
| colour manufacturer           | light gray (RAL 7035)                                                                 |
| material frame                | Powder-coated steel                                                                   |
| material tabletop             | Hard laminate                                                                         |
| with earthing point           | no                                                                                    |
| load capacity                 | 200 kg                                                                                |
| ESD safe                      | no                                                                                    |