

Suction arm system DN100 for wall/ceiling mounting, 3 joints, white, 2630 mm

Abbildung ähnlich



- All components RoHS compliant
- Design: suction arm for wall mounting
- Reach: 2630 mm
- Recommended air flow: 140 to 400 m³/h
- Pipe diameter: Ø100 mm
- With 2 gas springs
- POP® rivets made of acid-proof stainless steel (AISI 316L) ensure increased durability even when used in aggressive environments
- Pipes and joints made of chemically resistant polypropylene (PP)
- Joint color: white
- Maintenance-free O-rings made of polyethylene (PE)
- Integrated throttle valve, which is in open position out of the air flow to ensure maximum flow

- Threaded rods, springs and finger screws made of acid-proof stainless steel (AISI 316L)
- Protective grille available (accessory) to prevent foreign bodies from being sucked in
- Disassembly without tools for cleaning

item number	WL47171
model	100-135105-3-7-5
manufacturer	ALSIDENT
manufacturer item number	100-135105-3-7-5
GPSR manufacturer information	Alsident system A/S Finlandsvej 10 DK-8450 Hammel www.alsident.com
length	2630 mm
order unit	1 piece
content unit	1 piece
Colour	white
product series	Alsident System 100 CB
number of joints	3
range	2630 mm
diameter of tube	100 mm
air volume extraction arm	140 – 400 m ³ /h
assembling	wall mounting
joint colour	white
ESD safe	no

Other versions

item number	range
WL47170	2130 mm
WL47171	2630 mm