

ESD extraction arm system DN50 for wall/ceiling mounting, 2 joints, black, 530 mm

Alsident® System Antistatic (AS) is tested for use in ESD areas according to IEC 61340-5-1:2016. The extraction arms are grounded with a 1MΩ resistor.

- All components RoHS compliant
- Extraction arm for wall and ceiling mounting
- Reach: 530 mm
- Recommended air volume: 45 to 85 m³/h
- Pipe diameter (external): Ø 50 mm
- Tubes made of chromated TCP aluminum to ensure long-lasting conductivity
- Joints made of shock-resistant, conductive polypropylene (PP)
- Maintenance-free, conductive O-rings
- Integrated throttle valve, which is in open position out of the airflow to ensure maximum flow
- Threaded rods, springs and finger screws made of acid-proof stainless steel (AISI 316L)
- Acid resistant POP® rivets for increased durability even when used in aggressive environments
- Protective grids (accessories) to prevent foreign bodies from being sucked in
- Tested for use in ESD areas according to IEC 61340-5-1:2016
- The grounding cable has a 1 MΩ safety resistor
- Disassembly without tools for cleaning

Item no.	WL47495
Model	50-37-3-6
Manufacturer	ALSIDENT
Manufacturer article no.	50-37-3-6
GPSR manufacturer data	Alsident system A/S Finlandsvej 10 DK-8450 Hammel www.alsident.com
Length	530 mm
Sales unit	1 piece
Content unit	1 piece
Product series	Alsident System 50 AS
Number of joints	2
Reach	530 mm
Pipe diameter	50 mm

Products for the electronic industry



Air volume of the extraction arm	45 – 85 m ³ /h
Mounting type	ceiling mounting, wall mounting
Joint colour	black
ESD compliant	yes

