

ESD side trolley, max. load 200kg, with open frame, 605x405mm



Electrically conductive design (ESD = Electrostatic Discharge). Tubular steel and sectional steel welded, electrically conductive, powder coated slate grey RAL 7015. Shelves made of electrically conductive derived timber material board to DIN 68765, light grey. TPE-ESD tyres (thermoplastic elastomer) electrically conductive. Hubs with precision deep groove ball bearings. Locks on swivel castors, in accordance with EN 1757-3 (safety of platform trucks). Tubular and sectional steel construction. 2 swivel castors and 2 fixed castors, brakes on swivel castors. Load capacity upper and middle platform 50 kg. Open frame without panels.

| | |
|--------------|---------|
| Item no. | WL47797 |
| Model | 92900 |
| Manufacturer | FETRA |

Products for the electronic industry



| | |
|---------------------------------|---|
| Manufacturer article no. | 92900 |
| GPSR manufacturer data | fetra Fechtel Transportgeräte GmbH Industriestraße 17-21 DE-33829 Bogenhausen www.fetra.de |
| Length | 821 mm |
| Width | 455 mm |
| Height | 1178 mm |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Manufacturer colour information | slate grey |
| Colour | anthracite, grey |
| Material (frame) | Tubular steel |
| Incl. battery | no |
| Load capacity per shelf | 50 kg |
| Type of transport device | accessory trolley |
| Load capacity | 200 kg |
| Number of fixed castors | 2 |
| Number of swivel castors | 2 |
| Tires | TPE |
| Tire diameter | 125 mm |
| Bearing (tires) | ball bearing |
| Tire thickness | 32 mm |
| Length of the loading area | 605 mm |
| Width of the loading area | 405 mm |
| Number of shelves | 3 |
| Shelf height 1 | 197 mm |
| Shelf height 2 | 652 mm |
| Shelf height 3 | 1152 mm |
| ESD compliant | yes |