

Twistor16® self-adjusting crimping pliers for wire end ferrules with rotatable crimping head, chrome-plated, with multi-component sleeves, 260 mm



KNIPEX Twistor16® crimping head can be rotated freely through 360°, with 8 locking positions. Square crimp profile, high capacity range from 0.14 to 16 mm². Crimping of wire end ferrules possible from almost any working position. Crimping tool automatically adjusts to the different cross-sections. Accessible crimp opening on both sides, overlong wire-end ferrules can be pushed in. Crimping of twin wire-end ferrules up to 2 x 6 mm² possible. Consistently high crimp quality due to positive lock (can be unlocked). Lightweight and handy tool, manual force reinforced by toggle lever mechanism. - Application: Wire end ferrules - Capacity square millimetres: 0.14 - 16mm² - AWG: 26 - 5 - Number of nests: 1.

- Crimping tool automatically adjusts to the different cross-sections
- Accessible crimp opening on both sides, overlong wire end ferrules can be pushed in later
- Crimping of twin wire-end ferrules up to 2 x 6 mm² possible
- Consistently high crimp quality due to positive lock (can be unlocked)
- Light and handy tool, manual force reinforced by toggle lever mechanism

Item no.	WL50876
Model	97 53 18
Manufacturer	KNIPEX
Manufacturer article no.	97 53 18

Products for the electronic industry



GPSR manufacturer data

KNIPEX-Werk
 Oberkamper Strasse 13
 DE-42349 Wuppertal-Cronenberg
 www.knipex.de

Length	200 mm
Width	80 mm
Height	26 mm
Length with packaging	240 mm
Width with packaging	80 mm
Height with packaging	26 mm
Volume with packaging	0.499 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Product series	Twistor16®
RoHS compliant	no
Surface	chrome-plated
VDE	no
Crimping application	Wire end ferrules
Number of crimp nests	1
ESD compliant	no
AWG	26 - 5
Crimp profile	Square crimp
Tool length	260 mm
Grip (expression)	with multi-component sleeves
Type of pliers	automatic crimping tool