

Weller 576TX2 Side Cutter With Oval Head From Hard Metal Blades 110 Mm Flush 1.2 Mm, 65 °, 500 Micro Series



1 Million Movements - Magic Spring™ design enables maximum durability with constant spring force movements

Precision - Experience precise cuts from the high-precision screw joint that enables a smooth action with no jaw overlap

Uncompromising Swiss quality created to be strong, durable and sharp

Strong and Sharp - Hand-crafted cutting edges for superior strength and sharpness

Comfort, Security and Grip - Ergonomically-shaped handles provide superior comfort and fatigue-free handling with Maximum Opening Stop Technology

ESD Safe - made from ESD-safe material to prevent damage to sensitive components

Weller Erem® Cutters are designed to be strong, durable and sharp, having the highest precision available. Manufactured with uncompromising Swiss quality and created for worldwide applications, including electronics assembly and healthcare, Weller Erem

Cutters are built to last. The signature high-performance cutters set the industry standard

with features that include Weller Erem Magic Spring™ providing over one million consistent, precise and accurate movements, High-Precision Screw Joint, and Maximum Opening Stop Technology. Feel the difference with Weller Erem® – the proven choice. Every time. 1500 Weller Erem pneumatic side cutters are light and precise. Thanks to a selection of different cutting heads they can operate extremely versatile. The cutters are suitable for cutting conventional components, soft metals or small plastic parts. The cutting heads can be interchanged easily.

Item no.	WL51027
Manufacturer	Weller Erem
Manufacturer article no.	576TX2
GPSR manufacturer data	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
Sales unit	1 piece
Content unit	1 piece
VDE	no
Head width	11 mm
ESD compliant	yes
Head thickness	6 mm
Head length	17.5 mm
Tool length	110 mm
Type of side cutters	side cutter
Cutting length	9 mm
Cutting value wire diameter (hard)	0.5 mm
Cutting value wire diameter (medium)	0.8 mm
Cutting value wire diameter (soft)	1.2 mm