

ESD extraction arm system DN75 for wall/ceiling mounting, 3 joints, black, 1990 mm



Alsident® System 75 Antistatic is also approved for use in ESD/Ex areas (ATEX areas) according to the following standards: EN 80079-36-2016 and EN 80079-37-2016 and is therefore marked with: Ex II 1 GD. Alsident® System 75 Antistatic has therefore a ground wire mounted. For ESD areas, an earth lead with a 1MΩ resistor is also supplied.

- All components RoHS compliant
- Extraction arm for wall and ceiling mounting
- Reach: 1,990 mm
- Recommended air volume: 80 to 180 m³/h
- Tube diameter: Ø75 mm
- Pipes and joints made of shock-resistant, conductive, chemically resistant polypropylene
- Maintenance-free, conductive O-rings
- Integrated throttle valve, which is in open position out of the air flow to ensure maximum air flow

- Threaded rods, springs and finger screws made of acid-resistant stainless steel (AISI 316L)
- Rivets made of conductive, chemically resistant polypropylene (PP) for increased durability even when used in aggressive environments
- Protective grids (accessories) available for the hoods to prevent the ingestion of foreign bodies
- Tested for use in ESD areas according to IEC 61340-5-1:2016
- Tested for use in ESD/Ex areas according to EN 80079-36:2016 and EN 80079-37:2016 according to ATEX directive 2014/34/EU with marking Ex II 1 GD
- The grounding cable for ESD - 1 MΩ safety resistance - or EX areas is included in delivery
- Disassembly without tools for cleaning

Item no.	WL52675
Manufacturer	ALSIDENT
Manufacturer article no.	75-9090-3-22-6
GPSR manufacturer data	Alsident system A/S Finlandsvej 10 DK-8450 Hammel www.alsident.com
Length	1990 mm
Sales unit	1 piece
Content unit	1 piece
Colour	black
Product series	Alsident System 75 AL
Number of joints	3
Reach	1990 mm
Pipe diameter	75 mm
Air volume of the extraction arm	80 – 180 m ³ /h
Mounting type	ceiling mounting, wall mounting
Joint colour	black
ESD compliant	yes

Other versions

Item no.	Reach
WL28181	1660 mm
WL52675	1990 mm