

## Non-sparking 18 mm rolling copper beryllium wrench with center nut, 150 mm



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. 18 mm copper beryllium wrench with central nut, 150 mm.

- Made from copper beryllium
- Adjustable open-end wrench, spark-free, various opening widths adjustable
- Manufactured according to the specifications of the ISO 6787 standard
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Antimagnetic, extremely corrosion resistant

|                          |            |
|--------------------------|------------|
| item number              | WL52717    |
| model                    | NSB001-150 |
| manufacturer             | BAHCO      |
| manufacturer item number | NSB001-150 |
| length                   | 150 mm     |
| width                    | 61 mm      |
| height                   | 15 mm      |
| order unit               | 1 piece    |
| content unit             | 1 piece    |

|                |                                  |
|----------------|----------------------------------|
| VDE            | no                               |
| jaw thickness  | 8 mm                             |
| ESD safe       | no                               |
| tool material  | amagnetic steel, copperberyllium |
| packaging mass | piece                            |

## Other versions

| item number    | wrench width | length        |
|----------------|--------------|---------------|
| WL52760        | 6 mm         | 105 mm        |
| WL52763        | 7 mm         | 120 mm        |
| WL52766        | 8 mm         | 120 mm        |
| WL52768        | 9 mm         | 135 mm        |
| WL52725        | 10 mm        | 135 mm        |
| WL52726        | 11 mm        | 150 mm        |
| WL52727        | 12 mm        | 150 mm        |
| WL52728        | 13 mm        | 175 mm        |
| WL52729        | 14 mm        | 175 mm        |
| WL52730        | 15 mm        | 195 mm        |
| WL52731        | 16 mm        | 195 mm        |
| WL52732        | 17 mm        | 195 mm        |
| <b>WL52717</b> | <b>18 mm</b> | <b>150 mm</b> |
| WL52733        | 18 mm        | 215 mm        |
| WL52734        | 19 mm        | 215 mm        |
| WL52735        | 20 mm        | 215 mm        |
| WL52736        | 21 mm        | 245 mm        |
| WL52737        | 22 mm        | 245 mm        |
| WL52738        | 23 mm        | 265 mm        |
| WL52739        | 24 mm        | 265 mm        |
| WL52740        | 25 mm        | 265 mm        |
| WL52741        | 26 mm        | 290 mm        |
| WL52742        | 27 mm        | 290 mm        |
| WL52743        | 28 mm        | 290 mm        |
| WL52744        | 29 mm        | 320 mm        |

|         |       |        |
|---------|-------|--------|
| WL52745 | 30 mm | 320 mm |
| WL52746 | 31 mm | 340 mm |
| WL52747 | 32 mm | 340 mm |
| WL52748 | 33 mm | 340 mm |
| WL52749 | 34 mm | 360 mm |
| WL52750 | 35 mm | 360 mm |
| WL52751 | 36 mm | 360 mm |
| WL52752 | 38 mm | 430 mm |
| WL52753 | 40 mm | 430 mm |
| WL52754 | 41 mm | 430 mm |
| WL52755 | 42 mm | 430 mm |
| WL52756 | 46 mm | 480 mm |
| WL52757 | 50 mm | 520 mm |
| WL52758 | 52 mm | 520 mm |
| WL52759 | 55 mm | 560 mm |
| WL52761 | 60 mm | 595 mm |
| WL52762 | 65 mm | 595 mm |
| WL52764 | 70 mm | 630 mm |
| WL52765 | 75 mm | 630 mm |
| WL52767 | 80 mm | 660 mm |