

## Non-sparking 55 mm copper beryllium combination wrench, 560 mm



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. 55 mm open-end wrench made of copper beryllium, 560 mm.

- Made of copper beryllium
- Combination wrench, both sides with the same wrench size
- Ring side angled at 15°
- Manufactured according to the specifications of the DIN 3113 standard
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Ring side angled at 15°, for better working in places difficult to access
- Antimagnetic, extremely corrosion resistant

Item no.	WL52759
Model	NSB002-55
Manufacturer	BAHCO
Manufacturer article no.	NSB002-55
GPSR manufacturer data	BAHCO Werkzeuge Maybachstr. 10 DE-71711 Steinheim www.bahco-werkzeuge.de

Length	560 mm
Width	216 mm
Height	45 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
VDE	no
ESD compliant	no
Tool material	amagnetic steel, copperberyllium
Packaging dimensions	piece
Type of open-end wrench	Combination spanner
Wrench size	55 mm

## Other versions

Item no.	Wrench size	Length
WL52760	6 mm	105 mm
WL52763	7 mm	120 mm
WL52766	8 mm	120 mm
WL52768	9 mm	135 mm
WL52725	10 mm	135 mm
WL52726	11 mm	150 mm
WL52727	12 mm	150 mm
WL52728	13 mm	175 mm
WL52729	14 mm	175 mm
WL52730	15 mm	195 mm
WL52731	16 mm	195 mm
WL52732	17 mm	195 mm
WL52717	18 mm	150 mm
WL52733	18 mm	215 mm
WL52734	19 mm	215 mm
WL52735	20 mm	215 mm
WL52736	21 mm	245 mm
WL52737	22 mm	245 mm

WL52738	23 mm	265 mm
WL52739	24 mm	265 mm
WL52740	25 mm	265 mm
WL52741	26 mm	290 mm
WL52742	27 mm	290 mm
WL52743	28 mm	290 mm
WL52744	29 mm	320 mm
WL52745	30 mm	320 mm
WL52746	31 mm	340 mm
WL52747	32 mm	340 mm
WL52748	33 mm	340 mm
WL52749	34 mm	360 mm
WL52750	35 mm	360 mm
WL52751	36 mm	360 mm
WL52752	38 mm	430 mm
WL52753	40 mm	430 mm
WL52754	41 mm	430 mm
WL52755	42 mm	430 mm
WL52756	46 mm	480 mm
WL52757	50 mm	520 mm
WL52758	52 mm	520 mm
<b>WL52759</b>	<b>55 mm</b>	<b>560 mm</b>
WL52761	60 mm	595 mm
WL52762	65 mm	595 mm
WL52764	70 mm	630 mm
WL52765	75 mm	630 mm
WL52767	80 mm	660 mm