

## Non-sparking double open-end wrench, 16 x 18 mm, made of copper beryllium, 120 mm



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Double open ended wrench, 16 x 18 mm, made of copper beryllium, 120 mm.

- Made of copper beryllium
- Head angle: 15°
- Double open-end wrench, with two different widths
- Meets the product standards according to DIN 895
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Head angle of 15° for working in areas difficult to access
- Antimagnetic, extremely corrosion resistant

Item no.	WL52778
Model	NSB006-1012
Manufacturer	BAHCO
Manufacturer article no.	NSB006-1012

Products for the electronic industry



**GPSR manufacturer data**

BAHCO Werkzeuge  
 Maybachstr. 10  
 DE-71711 Steinheim  
 www.bahco-werkzeuge.de

Length	120 mm
Width	53 mm
Height	15 mm
Sales unit	1 piece
Content unit	1 piece
VDE	no
ESD compliant	no
Tool material	amagnetic steel, copperberyllium
Packaging dimensions	piece
Type of open-end wrench	Double open-end spanner
Wrench size	16 mm, 18 mm

**Other versions**

Item no.	Wrench size	Length
WL52772	1 mm, 9 mm	96 mm
WL52769	6 mm, 7 mm	92 mm
WL52798	6 mm, 7 mm	195 mm
WL52770	7 mm, 9 mm	95 mm
WL52771	8 mm, 9 mm	96 mm
WL52799	8 mm, 9 mm	200 mm
WL52773	10 mm, 11 mm	100 mm
WL52800	10 mm, 11 mm	200 mm
WL52774	10 mm, 12 mm	100 mm
WL52801	12 mm, 13 mm	210 mm
WL52775	12 mm, 14 mm	110 mm
WL52776	13 mm, 15 mm	110 mm
WL52802	14 mm, 15 mm	210 mm
WL52777	14 mm, 17 mm	115 mm
WL52803	16 mm, 17 mm	215 mm
<b>WL52778</b>	<b>16 mm, 18 mm</b>	<b>120 mm</b>

WL52779	17 mm, 19 mm	124 mm
WL52780	17 mm, 22 mm	124 mm
WL52781	18 mm, 19 mm	128 mm
WL52804	18 mm, 19 mm	220 mm
WL52782	19 mm, 21 mm	130 mm
WL52783	19 mm, 22 mm	128 mm
WL52784	20 mm, 22 mm	130 mm
WL52805	20 mm, 22 mm	230 mm
WL52785	21 mm, 23 mm	133 mm
WL52806	21 mm, 23 mm	230 mm
WL52786	22 mm, 24 mm	145 mm
WL52807	24 mm, 26 mm	230 mm
WL52787	24 mm, 27 mm	150 mm
WL52788	25 mm, 28 mm	150 mm
WL52808	25 mm, 28 mm	233 mm
WL52789	26 mm, 28 mm	157 mm
WL52809	27 mm, 29 mm	236 mm
WL52811	27 mm, 29 mm	250 mm
WL52790	27 mm, 30 mm	163 mm
WL52812	27 mm, 30 mm	250 mm
WL52791	27 mm, 32 mm	170 mm
WL52813	27 mm, 32 mm	243 mm
WL52814	28 mm, 30 mm	250 mm
WL52815	30 mm, 31 mm	265 mm
WL52792	30 mm, 32 mm	173 mm
WL52810	30 mm, 32 mm	250 mm
WL52816	30 mm, 32 mm	265 mm
WL52817	30 mm, 34 mm	270 mm
WL52793	30 mm, 36 mm	175 mm
WL52818	30 mm, 36 mm	270 mm
WL52819	32 mm, 34 mm	270 mm
WL52820	32 mm, 35 mm	300 mm
WL52794	32 mm, 36 mm	175 mm
WL52821	32 mm, 36 mm	300 mm
WL52822	33 mm, 35 mm	300 mm

WL52823	34 mm, 36 mm	300 mm
WL52824	35 mm, 36 mm	300 mm
WL52825	36 mm, 38 mm	330 mm
WL52795	36 mm, 41 mm	182 mm
WL52826	36 mm, 41 mm	330 mm
WL52827	38 mm, 42 mm	330 mm
WL52796	41 mm, 46 mm	185 mm
WL52828	41 mm, 46 mm	360 mm
WL52797	46 mm, 50 mm	190 mm
WL52829	46 mm, 50 mm	370 mm
WL52830	50 mm, 52 mm	375 mm
WL52831	50 mm, 55 mm	385 mm
WL52832	50 mm, 60 mm	400 mm
WL52833	50 mm, 62 mm	400 mm
WL52834	55 mm, 60 mm	415 mm
WL52835	60 mm, 65 mm	435 mm
WL52836	65 mm, 70 mm	480 mm