

Non-sparking double ring spanner, 24 x 27 mm, made of copper beryllium, 255 mm



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Double ring spanner, 24 x 27 mm, made of copper beryllium, 255 mm.

- Made of copper beryllium
- Double ring spanner with two different key widths
- Ideal for confined spaces and indentations
- Meets the product standards according to DIN 837
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Antimagnetic, extremely corrosion resistant

Item no.	WL52855
Model	NSB010-2427
Manufacturer	BAHCO
Manufacturer article no.	NSB010-2427
GPSR manufacturer data	BAHCO Werkzeuge Maybachstr. 10 DE-71711 Steinheim www.bahco-werkzeuge.de
Length	255 mm
Width	112 mm
Height	29 mm

Products for the electronic industry



Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
VDE	no
ESD compliant	no
Tool material	amagnetic steel, copperberyllium
Packaging dimensions	piece
Type of ring spanner	Doppler ring key
Wrench size	24 mm, 27 mm

Other versions

Item no.	Wrench size	Length
WL52837	6 mm, 7 mm	95 mm
WL52866	6 mm, 7 mm	115 mm
WL52838	7 mm, 9 mm	115 mm
WL52839	8 mm, 9 mm	115 mm
WL52840	9 mm, 11 mm	125 mm
WL52841	10 mm, 11 mm	140 mm
WL52842	10 mm, 12 mm	140 mm
WL52843	12 mm, 14 mm	145 mm
WL52844	13 mm, 15 mm	155 mm
WL52845	14 mm, 17 mm	165 mm
WL52846	16 mm, 18 mm	170 mm
WL52847	17 mm, 19 mm	185 mm
WL52848	17 mm, 22 mm	200 mm
WL52849	18 mm, 19 mm	185 mm
WL52850	19 mm, 21 mm	200 mm
WL52851	19 mm, 22 mm	200 mm
WL52852	20 mm, 22 mm	200 mm
WL52853	21 mm, 23 mm	220 mm
WL52854	22 mm, 24 mm	220 mm
WL52855	24 mm, 27 mm	255 mm
WL52856	25 mm, 28 mm	265 mm

WL52857	26 mm, 28 mm	265 mm
WL52858	27 mm, 30 mm	280 mm
WL52859	27 mm, 32 mm	295 mm
WL52860	30 mm, 32 mm	295 mm
WL52861	30 mm, 36 mm	330 mm
WL52862	32 mm, 36 mm	330 mm
WL52863	36 mm, 41 mm	365 mm
WL52864	41 mm, 46 mm	405 mm
WL52865	46 mm, 50 mm	425 mm

