

## 1/2" socket wrench insert made of copper beryllium, 23 mm hexagon profile, non-sparking



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. 1/2 socket wrench insert made of copper beryllium with 23 mm hexagonal profile, non-sparking.

- Made of copper beryllium
- Socket wrench inserts, standard length, 1/2"-square drive
- Hexagonal profile, metric sizes
- ISO 2725/1174
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Antimagnetic, extremely corrosion resistant

item number

WL53105

model

NSB220-23

Products for the electronic industry



manufacturer	BAHCO
manufacturer item number	NSB220-23
GPSR manufacturer information	BAHCO Werkzeuge Maybachstr. 10 DE-71711 Steinheim www.bahco-werkzeuge.de
length	44 mm
width	30 mm
height	30 mm
order unit	1 piece
content unit	1 piece
VDE	no
ESD safe	no
tool material	amagnetic steel, copperberyllium
packaging mass	piece
hexagon socket	23 mm

## Other versions

item number	hexagon socket
WL53088	6 mm
WL53089	7 mm
WL53090	8 mm
WL53091	9 mm
WL53092	10 mm
WL53093	11 mm
WL53094	12 mm
WL53095	13 mm
WL53096	14 mm
WL53097	15 mm
WL53098	16 mm
WL53099	17 mm
WL53100	18 mm
WL53101	19 mm
WL53102	20 mm

WL53103	21 mm
WL53104	22 mm
<b>WL53105</b>	<b>23 mm</b>
WL53106	24 mm
WL53107	25 mm
WL53108	26 mm
WL53109	27 mm
WL53110	28 mm
WL53111	29 mm
WL53112	30 mm
WL53113	32 mm

