

ERGO™ Screwdrivers made of copper beryllium for slotted screws, non-sparking, 2.5 x 10 x 200



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. ERGO™ Screwdrivers made of copper beryllium for slotted screws, non-sparking, 2.5 x 10 x 200 .

- Made of copper beryllium
- Developed according to the scientific ERGO™ process
- Screwdriver for slotted screws
- Handle made of antistatic plastic
- Manufactured according to the specifications of the ISO 2380 standard
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Three-component handle with strong core, provides a firm grip and maximum operating comfort with optimum power transmission
- Antimagnetic, extremely corrosion resistant

item number	WL53176
model	NSB300-10-200
manufacturer	BAHCO
manufacturer item number	NSB300-10-200
length	330 mm
width	40 mm
height	40 mm

order unit	1 piece
content unit	1 piece
handle length	120 mm
VDE	no
ESD safe	no
tool material	amagnetic steel, copperberyllium
packaging mass	piece
type of screwdriver	normal screwdrivers
Blade thickness	2.5 mm
Handle width	36 mm
blade length	200 mm
blade width	10 mm

Other versions

item number	blade length	Blade thickness	blade width
WL53183	50 mm	0.4 mm	3 mm
WL53186	60 mm	0.5 mm	4.5 mm
WL53184	75 mm	0.4 mm	3 mm
WL53187	75 mm	0.5 mm	4 mm
WL53189	75 mm	0.8 mm	5 mm
WL53185	95 mm	0.7 mm	4.5 mm
WL53188	100 mm	0.6 mm	5 mm
WL53190	105 mm	1 mm	6 mm
WL53191	125 mm	0.8 mm	6 mm
WL53193	150 mm	1 mm	7 mm
WL53194	150 mm	1.5 mm	8 mm
WL53192	160 mm	1.1 mm	6 mm
WL53195	200 mm	1.2 mm	8 mm
WL53176	200 mm	2.5 mm	10 mm
WL53196	250 mm	1.4 mm	9 mm
WL53178	250 mm	2 mm	11 mm
WL53179	300 mm	2 mm	11 mm
WL53177	318 mm	2.2 mm	10 mm

WL53180	350 mm	2 mm	11 mm
WL53181	400 mm	3 mm	12 mm
WL53182	450 mm	2.5 mm	13 mm