

ERGO™ Screwdrivers made of copper beryllium for slotted screws, non-sparking, 3 x 12 x 400



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. ERGO™ Screwdrivers made of copper beryllium for slotted screws, non-sparking, 3 x 12 x 400 .

- Made of copper beryllium
- Developed according to the scientific ERGO™ process
- Screwdriver for slotted screws
- Handle made of antistatic plastic
- Manufactured according to the specifications of the ISO 2380 standard
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Three-component handle with strong core, provides a firm grip and maximum operating comfort with optimum power transmission
- Antimagnetic, extremely corrosion resistant

item number	WL53181
model	NSB300-12-400
manufacturer	BAHCO
manufacturer item number	NSB300-12-400
length	535 mm
width	35 mm
height	35 mm

order unit	1 piece
content unit	1 piece
handle length	120 mm
VDE	no
ESD safe	no
tool material	amagnetic steel, copperberyllium
packaging mass	piece
type of screwdriver	normal screwdrivers
Blade thickness	3 mm
Handle width	36 mm
blade length	400 mm
blade width	12 mm

Other versions

item number	blade length	Blade thickness	blade width
WL53183	50 mm	0.4 mm	3 mm
WL53186	60 mm	0.5 mm	4.5 mm
WL53184	75 mm	0.4 mm	3 mm
WL53187	75 mm	0.5 mm	4 mm
WL53189	75 mm	0.8 mm	5 mm
WL53185	95 mm	0.7 mm	4.5 mm
WL53188	100 mm	0.6 mm	5 mm
WL53190	105 mm	1 mm	6 mm
WL53191	125 mm	0.8 mm	6 mm
WL53193	150 mm	1 mm	7 mm
WL53194	150 mm	1.5 mm	8 mm
WL53192	160 mm	1.1 mm	6 mm
WL53195	200 mm	1.2 mm	8 mm
WL53176	200 mm	2.5 mm	10 mm
WL53196	250 mm	1.4 mm	9 mm
WL53178	250 mm	2 mm	11 mm
WL53179	300 mm	2 mm	11 mm
WL53177	318 mm	2.2 mm	10 mm

WL53180	350 mm	2 mm	11 mm
WL53181	400 mm	3 mm	12 mm
WL53182	450 mm	2.5 mm	13 mm