

Sledge hammer with copper beryllium head and fiberglass handle, non-sparking, 12 kg



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Sledge hammer with copper beryllium head and fibreglass handle, non-sparking, 12 kg.

- Made of copper beryllium
- Two-component fibreglass handle
- Meets the product standards according to UNE 16590
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Without sharp edges, to avoid sparks
- Antimagnetic, extremely corrosion resistant

item number	WL53252
model	NSB502-12000-FB
manufacturer	BAHCO
manufacturer item number	NSB502-12000-FB
GPSR manufacturer information	BAHCO Werkzeuge Maybachstr. 10 DE-71711 Steinheim www.bahco-werkzeuge.de
length	900 mm

Products for the electronic industry



width	255 mm
height	90 mm
order unit	1 piece
content unit	1 piece
VDE	no
head width	85 mm
ESD safe	no
tool material	amagnetic steel, copperberyllium
packaging mass	piece
Hammer type	Sledge Hammer
Tool head weight	12 kg

Other versions

item number	Tool head weight & head width
WL53258	0.45 kg & 30 mm
WL53251	1 kg & 40 mm
WL53253	1.5 kg & 44 mm
WL53254	2 kg & 50 mm
WL53255	2.5 kg & 52 mm
WL53256	3 kg & 56 mm
WL53257	4.5 kg & 64 mm
WL53259	5 kg & 65 mm
WL53260	6.8 kg & 71 mm
WL53261	8 kg & 75 mm
WL53250	10 kg & 82 mm
WL53252	12 kg & 85 mm