

Sledge hammer with copper beryllium head and fiberglass handle, non-sparking, 6.8 kg



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Sledge hammer with copper beryllium head and fibreglass handle, non-sparking, 6.8 kg.

- Made of copper beryllium
- Two-component fibreglass handle
- Meets the product standards according to UNE 16590
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Without sharp edges, to avoid sparks
- Antimagnetic, extremely corrosion resistant

Article no.	WL53260
Model	NSB502-6800-FB
Manufacturer	BAHCO
Manufacturer article no.	NSB502-6800-FB
GPSR manufacturer data	BAHCO Werkzeuge Maybachstr. 10 DE-71711 Steinheim www.bahco-werkzeuge.de
Length	900 mm

Products for the electronic industry



Width	195 mm
Height	69 mm
Sales unit	1 piece
Content unit	1 piece
VDE	no
Head width	71 mm
ESD compliant	no
Tool material	amagnetic steel, copperberyllium
Packaging dimensions	piece
Tape of hammer	Sledge Hammer
Tool head weight	6.8 kg

Other versions

Article no.	Tool head weight & Head width
WL53258	0.45 kg & 30 mm
WL53251	1 kg & 40 mm
WL53253	1.5 kg & 44 mm
WL53254	2 kg & 50 mm
WL53255	2.5 kg & 52 mm
WL53256	3 kg & 56 mm
WL53257	4.5 kg & 64 mm
WL53259	5 kg & 65 mm
WL53260	6.8 kg & 71 mm
WL53261	8 kg & 75 mm
WL53250	10 kg & 82 mm
WL53252	12 kg & 85 mm