

Engineer's hammer with copper beryllium head and fibreglass handle, non-sparking, 300 g



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Engineer's hammer with copper beryllium head and fibreglass handle, non-sparking, 300 g.

- Made of copper beryllium
- Two-component fibreglass handle
- Meets the product standards according to DIN 1041
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Without sharp edges, to avoid sparks
- Antimagnetic, extremely corrosion resistant

item number	WL53267
model	NSB504-300-FB
manufacturer	BAHCO
manufacturer item number	NSB504-300-FB
length	280 mm
width	100 mm
height	28 mm

Products for the electronic industry



order unit	1 piece
content unit	1 piece
VDE	no
head width	23 mm
ESD safe	no
tool material	amagnetic steel, copperberyllium
packaging mass	piece
Hammer type	engineer's hammer
Tool head weight	0.3 kg

Other versions

item number	length	width	head width	Tool head weight
WL53263	280 mm	60 mm	16 mm	0.1 kg
WL53266	280 mm	80 mm	22 mm	0.2 kg
WL53267	280 mm	100 mm	23 mm	0.3 kg
WL53268	310 mm	112 mm	28 mm	0.5 kg
WL53269	355 mm	130 mm	33 mm	0.8 kg
WL53262	355 mm	135 mm	35 mm	1 kg
WL53264	400 mm	160 mm	40 mm	1.5 kg
WL53265	400 mm	170 mm	45 mm	2 kg