

Engineer's hammer with ball peen, copper beryllium head and fibreglass handle, non-sparking, 300 g



Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks. Engineer's hammer with ball tiller, copper beryllium head and fibreglass handle, non-sparking, 300 g.

- Made of copper beryllium
- Two-component fibreglass handle
- Meets the product standards according to UNE 16589
- Non-sparking tools are used in areas where there is a potential fire and explosion hazard due to flying sparks
- Without sharp edges, to avoid sparks
- Antimagnetic, extremely corrosion resistant

item number	WL53271
model	NSB506-300-FB
manufacturer	BAHCO
manufacturer item number	NSB506-300-FB
length	287 mm
width	110 mm
height	35 mm
order unit	1 piece

Products for the electronic industry



content unit	1 piece
VDE	no
head width	25 mm
ESD safe	no
tool material	amagnetic steel, copperberyllium
packaging mass	piece
Hammer type	English locksmith's hammer
Tool head weight	0.3 kg

Other versions

item number	length	width	head width	Tool head weight
WL53271	287 mm	110 mm	25 mm	0.3 kg
WL53273	313 mm	102 mm	26 mm	0.45 kg
WL53275	340 mm	115 mm	34 mm	0.68 kg
WL53277	365 mm	150 mm	36 mm	0.91 kg