

## ERGO™ Insulated screwdriver for slotted screws with 3-component handle, VDE-certified, slim blade 0.5 mm x 3 mm x 100 mm



- Developed as part of the ERGO™ process
- Insulated ERGO™ Screwdriver with slim blade for slotted screws
- The burnished tip ensures greater accuracy and good grip in the screw
- Three-component handle for maximum ease of use, soft material with ribbed surface for better grip and greater power transmission
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, sizes 3 and 3.5
- Flat sides prevent the screwdriver from rolling away
- Integrated suspension eye
- High-quality insulation layer, which is sprayed directly onto the blade
- The blades are 30% slimmer than conventional insulated blades and make it easier to work in hard-to-reach areas
- For work on live equipment up to 1000 V
- Standards: ISO 2380/DIN 5264
- Individually tested and manufactured according to IEC 60900, tested in a water bath at 10000 V

Item no.	WL53446
Model	BE 8220SL
Manufacturer	BAHCO

Manufacturer article no.	BE-8220SL
GPSR manufacturer data	BAHCO Werkzeuge Maybachstr. 10 DE-71711 Steinheim www.bahco-werkzeuge.de
Length	220 mm
Width	85 mm
Height	65 mm
Sales unit	1 piece
Content unit	1 piece
Handle length	103 mm
VDE	yes
Screw type	slot
ESD compliant	no
Packaging dimensions	piece
Screwdriver type	normal screwdrivers
Blade thickness	0.5 mm
Handle width	17 mm
Tool length	203 mm
Handle diameter	17 mm
Blade length	100 mm
Blade width	3 mm

## Other versions

Item no.	Blade length	Blade width & Blade thickness
<b>WL53446</b>	<b>100 mm</b>	<b>3 mm &amp; 0.5 mm</b>
WL53448	100 mm	3.5 mm & 0.6 mm
WL53435	100 mm	12 mm & 0.8 mm
WL53436	125 mm	5.5 mm & 1 mm
WL53454	150 mm	6.5 mm & 1.2 mm