

ERGO™ Screwdriver for slotted screws, straight, with 3-component handle, 0.6 mm × 3.5 mm × 200 mm



Maximum comfort with minimum effort due to ergonomic design

- Screwdriver developed in the course of the ERGO™ process
- For slotted screws
- Burnished tip for greater accuracy
- 3-component handle for maximum ease of use, soft material with rigid surface provides comfortable grip and better power transmission
- Maximum comfort with minimum effort due to ergonomic design
- The correct blade can be easily identified by the colour marking and the symbol on the end of the handle
- No colour identification in extra small handle, small sizes from 2 to 3.5
- Flat sides prevent rolling away
- integrated suspension opening
- High performance steel alloy blade, chrome plated and fully hardened for maximum corrosion protection and long life
- Standards: ISO 2380 and DIN 5264

item number	WL53449
model	BE 8235
manufacturer	BAHCO
manufacturer item number	BE-8235
length	330 mm
width	85 mm

Products for the electronic industry



height	40 mm
order unit	1 piece
content unit	1 piece
handle length	122 mm
VDE	no
type of screw	slot
ESD safe	no
packaging mass	piece
type of screwdriver	normal screwdrivers
Blade thickness	0.6 mm
Handle width	20 mm
tool length	322 mm
handle diameter	20 mm
blade length	200 mm
blade width	3.5 mm
blade thickness	0.6 mm

Other versions

item number	blade length	blade thickness	blade width
WL53430	60 mm	0.3 mm	2 mm
WL16075	60 mm	0.4 mm	2.5 mm
WL16077	60 mm	0.5 mm	3 mm
WL16086	75 mm	0.4 mm	2.5 mm
WL16078	75 mm	0.5 mm	3 mm
WL16079	75 mm	0.6 mm	3.5 mm
WL53432	100 mm	0.5 mm	3 mm
WL16080	100 mm	0.8 mm	4 mm
WL16087	125 mm	0.5 mm	3 mm
WL16089	125 mm	0.6 mm	3.5 mm
WL53450	125 mm	1 mm	5.5 mm
WL53688	150 mm	1 mm	5.5 mm
WL53452	150 mm	1 mm	6 mm
WL53689	150 mm	1.2 mm	6.5 mm

WL16090	175 mm	0.8 mm	4 mm
WL19948	175 mm	1.6 mm	8 mm
WL53447	200 mm	0.5 mm	3 mm
WL53449	200 mm	0.6 mm	3.5 mm
WL20734	200 mm	1 mm	5.5 mm