

Screwdriver Triton XLS slot, 3 x 75 mm, 164 mm

- Large 2-component triangular handle with soft grip inserts for comfortable working and optimum torque
- Blade injected directly into the handle ensures an absolutely stable connection for increased durability and reliability
- The angular shape of the handle prevents the screwdriver from rolling away on uneven surfaces
- Blade of hardened, high-alloy steel for durability
- Machine-made precision tips reduce the risk of breakage
- Colour coding and type identification at the end of the handle facilitate recognition
- Chrome-plated blades offer protection against rust
- The magnetic tip holds the screw securely, making placement and tightening easier
- According to ISO 2380-2
- Blade width: 3.0 mm
- Visible blade length: 75 mm
- total length: 164 mm

Item no.	WL53852
Model	T4725-030
Manufacturer	C.K
Manufacturer article no.	T4725-030
GPSR manufacturer data	Carl Kammerling International Bendahler Straße 110 DE-42285 Wuppertal www.ck-tools.com
Sales unit	1 piece
Content unit	1 piece
Standards	ISO 2380-2
VDE	no
Screw type	slot
ESD compliant	no
Screwdriver type	normal screwdrivers
Blade thickness	0.6 mm
Tool length	164 mm

Applications (screwdriver)	slotted screws
Blade length	75 mm
Blade width	3 mm

Other versions

Item no.	Blade width & Blade thickness
WL53852	3 mm & 0.6 mm
WL53853	4 mm & 0.8 mm
WL53854	5.5 mm & 1 mm