

ERGO™ side cutters with insulated handles, phosphated, 200 mm



Cutting radius runs along the edge so that hard materials such as piano wire can be cut close to the joint, but also soft materials

- Insulated handles of mono-material polypropylene
- For work on live equipment up to 1000 V according to IEC 60900
- Max. cutting capacity: 4.5 mm Cu, 3 mm Fe+ and 2.5 mm piano wire
- Distance between joint and cutting edges reduced for better leverage and maximum cutting capacity
- High Speed Steel
- Phosphated, anti-corrosion treated
- Cutting radius runs along the edge so that hard materials such as piano wire can be cut close to the joint, but also soft materials
- Bolted connection for excellent cutting performance and accuracy of fit of the cutting edges
- Rounded jaws for improved access to hard to reach areas
- Induction hardened cutting edges
- Durable, induction hardened cutting edge
- Each tool is tested for 10 seconds at 10,000 V at the end of the production process

item number	WL54853
model	2101S-200
manufacturer	BAHCO
manufacturer item number	2101S-200
length	200 mm
width	210 mm
height	28 mm
order unit	1 piece
content unit	1 piece
VDE	no
head width	25.5 mm
jaw thickness	2 mm
ESD safe	no
tool material	High performance steel alloy
packaging mass	piece
tool length	200 mm
type of side cutter	side cutter