

Open-ended spanner set insulated 6-32 mm 20 pcs. in case (43022)



- Increases your efficiency: Improved accessibility in narrow places due to 15° jaw position
- Offers you full protection: Each tool individually tested at 10,000 V AC and approved for 1,000 V AC
- Protects your material: Fully insulated tool reduces the risk of short circuits
- When working on live parts, the safety of the user is paramount. With the tool set including single open-ended spanner and rolling open-ended spanner, electricians and electrical specialists are ideally equipped for working on electrical systems. With a jaw position of 15°, the insulated single open-end wrenches are perfect for installing terminals and sockets in confined spaces. The roller spanner, which is also included, is variably adjustable and has a maximum opening width of 30 mm. Damage to sensitive surfaces is minimised by the particularly smooth and parallel jaws. The tools included in the set are subjected to routine testing in accordance with the international standard IEC 60900 and enable safe working in the vicinity of live parts up to 1,000 V AC.

- Application: Safe installation of terminals and sleeves, conductor connections, screwing of busbars. For working in the vicinity of live parts up to 1,000 V AC.

Alternative item description	5590NT20
item number	WL55212
model	5590NT20
manufacturer	WIHA
manufacturer item number	43022
scope of supply	1 x open-end spanner insulated (43026) 6 mm 1 x open-end spanner insulated (43027) 7 mm 1 x open-end spanner insulated (43028) 8 mm 1 x open-end spanner insulated (43029) 9 mm 1 x open-end spanner insulated (43030) 10 mm 1 x open-end spanner, insulated (43031) 11 mm 1 x open-end spanner, insulated (43032) 12 mm 1 x open-end spanner, insulated (43033) 13 mm 1 x open-end spanner, insulated (43034) 14 mm 1 x open-end spanner, insulated (43035) 15 mm 1 x open-end spanner, insulated (43036) 16 mm 1 x open-end spanner, insulated (43037) 17 mm 1 x open-end spanner, insulated (43038) 18 mm 1 x open-end spanner insulated (43039) 19 mm 1 x open-end spanner, insulated (43041) 24 mm 1 x open-end spanner, insulated (43042) 27 mm 1 x open-end spanner, insulated (43043) 1 x open-end spanner insulated (43044) 32 mm 1 x adjustable spanner electric 0-30 mm (43061) 0 - 30 mm
order unit	1 piece
content unit	1 piece
product series	5590N
VDE	no
ESD safe	no