

Single open-ended spanner insulated (43039) 19 mm



- Improves accessibility: Thanks to 15° jaw position, even screws in narrow places can be reached without difficulty
- Offers you full protection: Each tool individually tested at 10,000 V AC and approved for 1,000 V AC
- Protects your material: Fully insulated tool reduces the risk of short circuits
- When working on live parts, user safety is paramount. The insulated single open-ended spanner is the optimum tool for electricians and electrical specialists. With a jaw position of 15°, the installation of terminals and sleeves in confined spaces is child's play. The insulated open-ended spanner is subjected to routine testing in accordance with the international standard IEC 60900 and enables safe working in the vicinity of live parts up to 1,000 V AC.
- Application: Safe installation of terminals and sleeves, conductor connections, screwing of busbars. For working in the vicinity of live parts up to 1,000 V AC.

Item no.	WL55277
Model	246170
Alternative article name	246170
Manufacturer	WIHA
Manufacturer article no.	43039
GPSR manufacturer data	Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com
Sales unit	1 piece
Content unit	1 piece

Products for the electronic industry



Incl. battery	no
Product series	5590N
VDE	no
ESD compliant	no
Wrench size	19 mm
Wrench size	19 mm

Other versions

Item no.	Wrench size
WL55281	6 mm
WL55282	7 mm
WL55283	8 mm
WL55284	9 mm
WL55268	10 mm
WL55269	11 mm
WL55270	12 mm
WL55271	13 mm
WL55272	14 mm
WL55273	15 mm
WL55274	16 mm
WL55275	17 mm
WL55276	18 mm
WL55277	19 mm