

Safety shoe Duo Soft 765 2.0, S3, smooth leather, unisex, black, size 45



At ATLAS®, only the best quality cowhides are processed. Extremely careful selection ensures that only flawless, high-quality and soft leathers are used. The ATLAS Waterproof smooth leather has to withstand special challenges throughout the entire working day. The approx. 2mm thick full-grain cowhide leather is particularly characterised by its lasting waterproofness and thus ensures dry feet for several hours. It is also particularly breathable, durable and dimensionally stable.

Pointed objects, high temperatures and liquid materials are not uncommon in the heavy and chemical industries, in metalworking companies or in hot areas. With its DUOSOFT sole technology, ATLAS has developed an outsole concept that is precisely tailored to the needs of these working environments. In addition to the thermal insulation of the sole complex (HI) and the behaviour of the outsole towards contact heat (HRO), a certain cut resistance and robustness is also of particular importance. The individual tread blocks offer

maximum flexibility for optimum ground contact. The coarse tread with a depth of 4.5mm significantly reduces the risk of slipping on wet or frozen ground. With the latest production technology, the perfect combination of nitrile outsole and MPU® midsole is produced using the direct foaming process, thus giving the wearer a secure step.

The anti-puncture steel midsole is made of corrosion-resistant stainless steel and protects the foot against sharp objects such as nails. It has been optimally adapted to the last fit and foamed into the midsole material. This means that you are optimally protected even during long and hard indoor and outdoor use.

The anatomically shaped steel toe cap protects the foot in the toe area against impact of min. 200 joules and a compressive stress of min. 15 kN, according to EN ISO 20345:2012.

The overcap offers special protection against abrasion in the area of the shoe toe, protects the upper leather in this area against premature wear and noticeably increases the service life of the safety shoe.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS® enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interaction of a pressure-relieving insole and the light and responsive MPU sole technology.

geeignet für die Einlagenversorgung-DGUV 112-191

ATLAS® offers you a wide range of different orthopaedic insoles. The articles marked here are suitable for orthopaedic insoles according to DGUV regulation 112-191. The marking on the shoe is decisive for this.

item number	WL56198
model	Duo Soft 765 2.0
model line	Duo Soft 765 2.0
manufacturer	ATLAS
manufacturer item number	8300-45
length with packaging	350 mm
width with packaging	250 mm
height with packaging	150 mm
order unit	1 pair
content unit	1 pair
colour manufacturer	black

Colour	black
protective cap	yes
shoe execution	safety shoe
safety class	S3
shoe sole	DuoSoft sole technology
Slip resistance	SRC
Puncture resistance	penetration inhibition
shoe width	W10 (standard width)
features shoes	<ul style="list-style-type: none"> • Waterproof smooth leather • DuoSoft sole technology • penetration inhibition • Steel toe cap • Overcap • active-X functional lining • 3D cushioning system • suitable for insoles-DGUV 112-191
material shoes	waterproof smooth leather
shoe size EU	45
Category (PPE Regulation)	Category 2

Other versions

item number	shoe size EU	shoe width
WL56192	37	W10 (standard width)
WL56202	37	W12
WL56193	38	W10 (standard width)
WL56203	38	W12
WL56194	39	W10 (standard width)
WL56204	39	W12
WL56195	40	W10 (standard width)
WL56205	40	W12
WL56196	41	W10 (standard width)
WL56206	41	W12
WL56197	42	W10 (standard width)
WL56207	42	W12
WL33926	43	W10 (standard width)
WL56208	43	W12

WL44158	44	W10 (standard width)
WL56209	44	W12
WL56198	45	W10 (standard width)
WL56210	45	W12
WL56199	46	W10 (standard width)
WL56211	46	W12
WL56200	47	W10 (standard width)
WL56212	47	W12
WL56201	48	W10 (standard width)
WL56213	48	W12

