

Low shoe ERGO-MED 600 2.0, W10, S2, nubuck leather, unisex, black/royal blue, size 40



At ATLAS®, only the best quality cowhides are processed. Extremely careful selection ensures that only flawless, high-quality and soft leathers are used. The ATLAS SOFT nubuck leather has to withstand special challenges throughout the entire working day. The approx. 2mm thick full-grain cowhide leather is particularly characterised by its breathability and soft, comfortable feel.

ATLAS® brings together state-of-the-art technologies and the anatomical needs of every wearer. The new INNOFLEX SYSTEM® is a holistic running sole concept and supports the runner in every phase of movement. From the first to the last contact with the ground, the sole complex is permanently guided by the same, natural line of force, the INNOFLEX LINE. It optimally guides the forces from the heel to the toe and thus supports the natural line of force progression. Special areas such as the CLOUDZONE in the heel are responsible for the corresponding energy absorption, i.e. cushioning. The large-format tread surfaces, which are equipped with particularly energy-absorbing MPU® material,











absorb the energy and return it to the movement process in a targeted manner. This guarantees fatigue-free walking throughout the entire working day.

The anatomically shaped steel toe cap protects the foot in the toe area against impact of min. 200 joules and a compressive stress of min. 15 kN, according to EN ISO 20345:2012.

Especially when kneeling, wear and tear can occur in the area of the shoe toe after some time. These can be significantly reduced with the help of the abrasion-resistant MPU toe protector and the service life of the shoe is thus increased.

Particularly in everyday working life, with high physical stress, temperature-regulating properties are not only required, but expected. The aktiv-X functional lining stands for the highest quality, innovative technology and offers the wearer permanent, active moisture regulation. The aktiv-X functional lining regulates moisture and ensures that the shoes dry again quickly. It does not stain, is skin-friendly and abrasion-resistant.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS® enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interaction of a pressure-relieving insole and the light and responsive MPU sole technology.

geeignet für die Einlagenversorgung und zur Herstellung orthopädischer Zurichtungen (Sohlen- und Absatzerhöhungen) gemäß DGUV 112-191

ATLAS offers the models from the Ergo-Med series for orthopaedic care through shoe modifications. The articles marked with "blueline" are also suitable for certified orthopaedic modifications according to DGUV regulation 112-191.

| item number | WL56541 |
|--------------------------|-----------------------|
| model | ERGO-MED 600 2.0, W10 |
| model line | ERGO-MED 600 2.0 |
| manufacturer | ATLAS |
| manufacturer item number | 86700-40 |
| length with packaging | 350 mm |
| width with packaging | 250 mm |
| height with packaging | 150 mm |
| order unit | 1 pair |
| content unit | 1 pair |
| colour manufacturer | black / royal blue |

Products for the electronic industry













| Colour | blue, black |
|---------------------------|---|
| protective cap | yes |
| shoe execution | low shoe |
| safety class | S2 |
| shoe sole | MPU INNOFLEX system |
| Slip resistance | SRC |
| shoe width | W10 (standard width) |
| features shoes | SOFT nubuck leather MPU INNOFLEX system Steel toe cap and MPU toe protection MPU lace protection active-X functional lining 3D cushioning system suitable for the supply of insoles and for the production of orthopedic adjustments (sole and heel elevations) according to DGUV 112-191 |
| material shoes | Nubuk-leather |
| shoe size EU | 40 |
| Category (PPE Regulation) | Category 2 |
| | |

Other versions

| item number | shoe size EU | shoe width |
|-------------|--------------|----------------------|
| WL56537 | 36 | W10 (standard width) |
| WL56552 | 36 | W12 |
| WL56567 | 36 | W13 |
| WL56582 | 36 | W14 |
| WL56538 | 37 | W10 (standard width) |
| WL56553 | 37 | W12 |
| WL56568 | 37 | W13 |
| WL56583 | 37 | W14 |
| WL56539 | 38 | W10 (standard width) |
| WL56554 | 38 | W12 |
| WL56569 | 38 | W13 |
| WL56584 | 38 | W14 |
| WL56540 | 39 | W10 (standard width) |
| WL56555 | 39 | W12 |

Products for the electronic industry













| WL56570 | 39 | W13 |
|---------|----|----------------------|
| WL56585 | 39 | W14 |
| WL56541 | 40 | W10 (standard width) |
| WL56556 | 40 | W12 |
| WL56571 | 40 | W13 |
| WL56586 | 40 | W14 |
| WL56542 | 41 | W10 (standard width) |
| WL56557 | 41 | W12 |
| WL56572 | 41 | W13 |
| WL56587 | 41 | W14 |
| WL56543 | 42 | W10 (standard width) |
| WL56558 | 42 | W12 |
| WL56573 | 42 | W13 |
| WL56588 | 42 | W14 |
| WL56544 | 43 | W10 (standard width) |
| WL56559 | 43 | W12 |
| WL56574 | 43 | W13 |
| WL56589 | 43 | W14 |
| WL56545 | 44 | W10 (standard width) |
| WL56560 | 44 | W12 |
| WL56575 | 44 | W13 |
| WL56590 | 44 | W14 |
| WL56546 | 45 | W10 (standard width) |
| WL56561 | 45 | W12 |
| WL56576 | 45 | W13 |
| WL56591 | 45 | W14 |
| WL56547 | 46 | W10 (standard width) |
| WL56562 | 46 | W12 |
| WL56577 | 46 | W13 |
| WL56592 | 46 | W14 |
| WL56548 | 47 | W10 (standard width) |
| WL56563 | 47 | W12 |
| WL56578 | 47 | W13 |
| WL56593 | 47 | W14 |
| WL56549 | 48 | W10 (standard width) |
| | | |

Products for the electronic industry













| WL56564 | 48 | W12 |
|---------|----|----------------------|
| WL56579 | 48 | W13 |
| WL56594 | 48 | W14 |
| WL56550 | 49 | W10 (standard width) |
| WL56565 | 49 | W12 |
| WL56580 | 49 | W13 |
| WL56595 | 49 | W14 |
| WL56551 | 50 | W10 (standard width) |
| WL56566 | 50 | W12 |
| WL56581 | 50 | W13 |
| WL56596 | 50 | W14 |











5/5