

ESD safety shoe SL 805 XP blue 2.0 W12, S3, nubuck leather, unisex, black/royal blue, size 47



At ATLAS®, only the best quality cowhides are processed. Extremely careful selection ensures that only flawless, high-quality and soft leathers are used. The ATLAS SOFT nubuck leather has to withstand special challenges throughout the entire working day. The approx. 2mm thick full-grain cowhide leather is particularly characterised by its breathability and soft, comfortable feel.

ATLAS® brings together state-of-the-art technologies and the anatomical needs of every wearer. The new INNOFLEX SYSTEM® is a holistic running sole concept and supports the runner in every phase of movement. From the first to the last contact with the ground, the sole complex is permanently guided by the same, natural line of force, the INNOFLEX LINE. It optimally guides the forces from the heel to the toe and thus supports the natural line of force progression. Special areas such as the CLOUDZONE in the heel are responsible for the corresponding energy absorption, i.e. cushioning. The large-format

tread surfaces, which are equipped with particularly energy-absorbing MPU® material, absorb the energy and return it to the movement process in a targeted manner. This guarantees fatigue-free walking throughout the entire working day.

With the puncture-resistant XP® technology, ATLAS® offers an innovative system to protect the foot against sharp objects such as nails. A high-tech textile material containing aramid fibres is used for this purpose. The increased safety is not at the expense of wearing comfort, because the textile is metal-free, extremely light and supports the natural torsion of the foot.

Alu-tec® technology: The new lightness. Aluminium has not only served as a high-tech material in aviation and the automotive industry for years, but also in many ATLAS safety shoes today. The anatomically shaped aluminium toe cap is particularly light and shifts the centre of gravity of the shoe to the middle of the foot. This actively helps to prevent tripping accidents caused by imbalance. The thermally neutral behaviour of aluminium also prevents cold bridges from forming inside the shoe and thus guarantees a pleasant foot climate in all seasons.

Especially when kneeling, wear and tear can occur in the area of the shoe toe after some time. These can be significantly reduced with the help of the abrasion-resistant MPU toe protector and the service life of the shoe is thus increased.

Particularly in everyday working life, with high physical stress, temperature-regulating properties are not only required, but expected. The aktiv-X functional lining stands for the highest quality, innovative technology and offers the wearer permanent, active moisture regulation. The aktiv-X functional lining regulates moisture and ensures that the shoes dry again quickly. It does not stain, is skin-friendly and abrasion-resistant.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS® enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interaction of a pressure-relieving insole and the light and responsive MPU sole technology.

geeignet für die Einlagenversorgung-DGUV 112-191

ATLAS® offers you a wide range of different orthopaedic insoles. The articles marked here are suitable for orthopaedic insoles according to DGUV regulation 112-191. The marking on the shoe is decisive for this.

Item no.

WL58650

Model

SL 805 XP blue 2.0 W12 ESD

Products for the electronic industry



WL58625	36	W10 (standard width)
WL58639	36	W12
WL58626	37	W10 (standard width)
WL58640	37	W12
WL58627	38	W10 (standard width)
WL58641	38	W12
WL58628	39	W10 (standard width)
WL58642	39	W12
WL58629	40	W10 (standard width)
WL58643	40	W12
WL58630	41	W10 (standard width)
WL58644	41	W12
WL58631	42	W10 (standard width)
WL58645	42	W12
WL58632	43	W10 (standard width)
WL58646	43	W12
WL58633	44	W10 (standard width)
WL58647	44	W12
WL58634	45	W10 (standard width)
WL58648	45	W12
WL58635	46	W10 (standard width)
WL58649	46	W12
WL58636	47	W10 (standard width)
WL58650	47	W12
WL58637	48	W10 (standard width)
WL58651	48	W12
WL58638	49	W10 (standard width)
WL58652	49	W12