

HDPN-50-C Test Torque Meter



- Torque accuracy: +/- 0.5% of full scale value
- Certificate of calibration traceable to N.I.S.T.
- Data output and analogue output
- Reads clockwise and counterclockwise
- Min, max and average of last 10 torque readings provided
- 3 operating modes: Track, Peak, First Peak
- Up to 100 readings stored in memory
- Multiple functions: Auto Reset, Manual Reset, Auto Send to Printer, Manual Send to Printer
- Battery pack/charge time: 1.2V NiMH x 5 cells, 1,000mA (within 6 hours)
- Continuous operating time on a full charge: 8 hours
- Battery life: approx. 300 charges
- Find the failure point for fasteners and find the failure point for the hole
- Audible warning tone can be set to alert the operator when the desired torque is approaching

- Measure fastener, bottle cap or other container loosening torque, shear strength and material strength
- 220V available, contact ASG for more information
- Each HDP torque tester includes the following:
- Battery charger: 7.3-8 V, 500mA 110-240 VAC (US) style wall plug.
- Assorted bits
- Carrying case

item number	WL59818
model	HDPN-50-C
manufacturer	HIOS
manufacturer item number	050128-CE
length	125 mm
width	95.6 mm
height	42 mm
order unit	1 piece
content unit	1 piece
with battery	yes
Torque Nm	0,15 - 5,00 Nm
ESD safe	no