

## ESD Euro box trolley, max. load 300kg, with 5 open shelf frames for 3 Euro boxes each, 1240x610mm



Electrically conductive design (ESD = Electrostatic Discharge). Tubular steel and sectional steel welded, electrically conductive, powder coated slate grey RAL 7015. Screw construction. Shelves made of electrically conductive derived timber material board to DIN 68765, light grey. 4 swivel castors with TPE-ESD tyres (thermoplastic elastomer), electrically conductive. Hubs with precision deep groove ball bearings. 2 with wheel stops, in accordance with EN 1757-3 (safety of platform trolleys). 5 shelf frames for 3 Euro boxes 600 x 400 mm each, can be screwed in variably, grid 100 mm, inclination for sloping installation 15° or 30°. Load capacity per platform 80 kg.

item number	WL60157
manufacturer	FETRA
manufacturer item number	9383

Products for the electronic industry



length	1372 mm
width	685 mm
height	1686 mm
order unit	1 piece
content unit	1 piece
colour manufacturer	slate grey
Colour	anthracite, grey
material frame	Tubular steel
load capacity per shelf	80 kg
model transport trolley	shelf trolley
load capacity	300 kg
number of swivel castors	4
tyres	TPE
tyre diameter	160 mm
wheel bearing	ball bearing
tyre width	40 mm
load platform length	1240 mm
load platform width	610 mm
number of shelves	5
shelf heigth 1	298 mm
shelf heigth 2	598 mm
shelf height 3	898 mm
shelf height 4	1198 mm
shelf height 5	1498 mm
ESD safe	yes