

## ESD box trolley, electrically conductive with double wing door and shoot bolt lock, 1200x780mm



ESD box trolley of angle steel construction with tubular push handle. End walls, 1 longitudinal wall and roof covered with wire mesh 40 x 40 x 4 mm, completely welded, electrically conductive powder coated, slate grey RAL 7015. With double hinged door made of angle steel with welded wire mesh on the open longitudinal side. With espagnolette lock with swivel lever and cylinder lock. 1 fixed and 4 loose shelves made of electrically conductive derived timber material board to DIN 68765, light grey. 2 swivel castors and 2 fixed castors, wheels with ESD TPE tyres (thermoplastic elastomer), electrically conductive. Hubs with precision grooved ball bearings. Maximum comfort: very low starting, rolling and swivelling resistance. Low-noise running on even floors. Non-marking tyres. TOTALSTOP central braking system as standard on swivel castors.

item number

WL60241

Products for the electronic industry



|                               |   |
|-------------------------------|---|
| manufacturer                  | FETRA   |
| manufacturer item number      | 9393  |
| GPSR manufacturer information | fetra Fechtel Transportgeräte GmbH<br>Industriestraße 17-21<br>DE-33829 Bogenhausen<br>www.fetra.de |
| length                        | 1370 mm   |
| width                         | 845 mm  |
| height                        | 1792 mm   |
| order unit                    | 1 piece   |
| content unit                  | 1 piece   |
| colour manufacturer           | slate grey  |
| Colour                        | anthracite, grey  |
| material frame                | Angle steel   |
| load capacity per shelf       | 50 kg   |
| model transport trolley       | box trolley   |
| load capacity                 | 750 kg  |
| number of fixed castors       | 2   |
| number of swivel castors      | 2   |
| tyres                         | TPE   |
| tyre diameter                 | 200 mm  |
| wheel bearing                 | ball bearing  |
| tyre width                    | 40 mm   |
| load platform length          | 1200 mm   |
| load platform width           | 780 mm  |
| number of shelves             | 5   |
| shelf height 1                | 292 mm  |
| shelf height 2                | 582 mm  |
| shelf height 3                | 882 mm  |
| shelf height 4                | 1182 mm   |
| shelf height 5                | 1482 mm   |
| ESD safe                      | yes   |