Dump truck, 250 litre capacity, up to 750 kg load capacity, with drain tap



Tilting trough made of 2 mm thick sheet steel, top edge folded over twice, double folded over pouring edge, oil-tight welded. Base frame made of 3 mm thick edge profiles with integrated forklift pockets. Step plate and anti-tip device, tubular push handle. Powder coating anthracite grey RAL 7016. 2 swivel and 2 fixed castors, TPE tyres, hubs with deep groove ball bearings. TOTALSTOP central braking system as standard on swivel castors, in accordance with European standard EN 1757-3 (safety of platform trucks). Mobile and for forklift operation. With drain cock with sieve for separating liquids and solids. Tilting process is triggered manually. For emptying with a forklift truck or for heavy loads, we recommend a tipping container or a self-tipper.

Item no.	**WL60267**
Manufacturer	FETRA
Manufacturer article no.	4701A-7016

GPSR manufacturer data	fetra Fechtel Transportgeräte GmbH Industriestraße 17-21 DE-33829 Bogenhausen www.fetra.de
Length	1359 mm
Width	713 mm
Height	780 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	anthracite grey
Colour	anthracite, grey
Contents (liters)	250 l
Material	Sheet steel, edge profiles
Type of transport device	dump truck
Load capacity	750 kg
Number of fixed castors	2
Number of swivel castors	2
Tires	TPE
Tire diameter	200 mm
Bearing (tires)	ball bearing
Tire thickness	40 mm
ESD compliant	no