

Shelf trolley with hinged doors, max. load 600kg, 5 shelves, 1800mm high, 1200x800mm



Modular system, tubular steel and sectional steel welded, powder coated blue RAL 5007, bolted construction. End walls and one longitudinal wall closed with wire mesh 100 x 100 x 5 mm. With one double wing door, tubular steel frame with welded wire mesh 100 x 100 x 5 mm. Bolt lock integrated in the tubular frame, lockable with padlock (not included), door wings can be folded against the end walls. With wire mesh roof. 1 fixed and 4 loose shelves made of derived timber material board, surface beech decor. Shelves can be used variably, pitch 100 mm. Max. load per shelf 90 kg. Wheels: 2 swivel castors and 2 fixed castors, TPE tyres, hubs with deep groove ball bearings. Locks on swivel castors, in accordance with European standard EN 1757-3 (safety of platform trucks).

Article no.

WL60273

Manufacturer

FETRA

Products for the electronic industry



Manufacturer article no.	8583-3DE
GPSR manufacturer data	fetra Fechtel Transportgeräte GmbH Industriestraße 17-21 DE-33829 Bogenhausen www.fetra.de
Length	1369 mm
Width	830 mm
Height	1800 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	brilliant blue
Colour	blue
Material (frame)	Tubular steel
Load capacity per shelf	90 kg
Type of transport device	shelf trolley
Load capacity	600 kg
Number of fixed castors	2
Number of swivel castors	2
Tires	TPE
Tire diameter	200 mm
Bearing (tires)	ball bearing
Tire thickness	40 mm
Length of the loading area	1200 mm
Width of the loading area	800 mm
Number of shelves	5
Shelf height 1	269 mm
Shelf height 2	569 mm
Shelf height 3	869 mm
Shelf height 4	1169 mm
Shelf height 5	1469 mm
ESD compliant	no