

Ramp section, X-LOG, yellow, 500x90x7 mm, 1 piece



The 7mm thick X Joint ramp edge is designed to create a safe, sloped ramp onto your ESD floor tiles. Each ramp connects to a tile using the standard tap together interlocking joint. We recommend you use ramp edges in doorways and large entrances like shutters to eliminate trip hazards.

One ramp is 500mm wide and connects seamlessly with a full tile.

Important: Please note the installation instructions for ecotile floor tiles. These instructions are available under "Documents" > "Download technical data sheet".

- Manufactured in UK under ISO9001 standards
- Made from REACH compliant PVC
- EN 1081, EN 1815 & EN6356
- Surface resistance of the tiles is between 3.0×10^4 Ohm/m² and 3×10^6 Ohm
- Contact resistance of the tiles is between 3.6×10^5 Ohm and 9.5×10^5 Ohm
- Fire retardant - class Bfl s1
- Slip-resistant

- Chemical-resistant
- Reduces dust and noise
- Click-and-use installation
- Insulation of the floor against cold and humidity

item number	WL60309
manufacturer	ECOTILE
manufacturer item number	X57.601/1
length	90 mm
width	500 mm
height	7 mm
order unit	1 piece
content unit	1 piece
Colour	yellow
surface texture	flat
type of lining	floor ramp
ESD safe	yes