

## Floor marking tile with ESD logo, X-Lock, yellow, 497 x 497 x 7 mm, 1 piece



ESD pictogram, floor tile approx. 497 x 497 mm, thickness 7 mm, new X-Lock connection, ATTENTION: visual character only, tile not available in ESD version.

Note: Please follow the laying instructions for ecotile floor tiles. This is available under "Documents" > "Download technical data sheet".

- Manufactured in UK under ISO9001 standards
- Made from REACH compliant PVC
- 497mm x 497mm x 7mm
- EN 1081, EN 1815 & EN6356
- Surface resistance of the tiles is between  $3.0 \times 10^4$  Ohm/m<sup>2</sup> and  $3 \times 10^6$  Ohm
- Contact resistance is between  $3.6 \times 10^5$  Ohm and  $9.5 \times 10^5$  Ohm
- Fire retardant - class Bfl s1
- Slip-resistant

- Chemical-resistant
- Reduces dust and noise
- Click-and-use installation
- Insulation of the floor against cold and humidity

<b>Item no.</b>	<b>WL60406</b>
Manufacturer	ECOTILE
Manufacturer article no.	13.2322 / 7 MM
GPSR manufacturer data	ecotile Flooring Sedgwick Road Unit 15 GB-LU4 9DT Luton www.ecotileflooring.com
Length	497 mm
Width	497 mm
Height	7 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	yellow (RAL 1023)
Colour	yellow
Connection system	X-Lock
Surface texture	flat
Strength	7 mm
Type of surface	Floor tile with marking
ESD compliant	no

## Other versions

Item no.	Strength
WL86106	5 mm
<b>WL60406</b>	<b>7 mm</b>