

Floor marking tile with ESD logo, X-Lock, yellow, 497 x 497 x 7 mm, 1 piece



ESD pictogram, floor tile approx. 497 x 497 mm, thickness 7 mm, new X-Lock connection, ATTENTION: visual character only, tile not available in ESD version.

- Manufactured in UK under ISO9001 standards
- Made from REACH compliant PVC
- 497mm x 497mm x 7mm
- EN 1081, EN 1815 & EN6356
- Surface resistance of the tiles is between 3.0×10^4 Ohm/m² and 3×10^6 Ohm
- Contact resistance is between 3.6×10^5 Ohm and 9.5×10^5 Ohm
- Fire retardant - class Bfl s1
- Slip-resistant
- Chemical-resistant

- Reduces dust and noise
- Click-and-use installation
- Insulation of the floor against cold and humidity

Item no.	WL60406
Manufacturer	ECOTILE
Manufacturer article no.	13.2322 / 7 MM
GPSR manufacturer data	ecotile Flooring Sedgwick Road Unit 15 GB-LU4 9DT Luton www.ecotileflooring.com
Length	497 mm
Width	497 mm
Height	7 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	yellow (RAL 1023)
Colour	yellow
Incl. battery	no
Connection system	X-Lock
Surface texture	flat
Strength	7 mm
Type of surface	Floor tile with marking
ESD compliant	no

Other versions

Item no.	Strength
WL86106	5 mm
WL60406	7 mm