

## ESD earthing tile, X-Lock, light gray, 497 x 497 x 7 mm, 1 piece

---



The 7 mm ESD X-Lock earthing tile is used every 50 square meters. The earthing tile can be connected to the earth via an earthing cable to an earthing plug or earthing rail in accordance with the installation instructions.

Note: Please observe the installation instructions for ecotile floor tiles. These are available under "Documents" > "Download technical data sheet".

- Manufactured in UK under ISO9001 standards
- Made from REACH compliant PVC
- 497mm x 497mm x 7mm
- EN 1081, EN 1815 & EN6356
- Surface resistance of the tiles is between  $3.0 \times 10^4$  Ohm/m<sup>2</sup> and  $3 \times 10^6$  Ohm
- Contact resistance is between  $3.6 \times 10^5$  Ohm and  $9.5 \times 10^5$  Ohm
- Fire retardant - class Bfl s1
- Slip-resistant
- Chemical-resistant

- Reduces dust and noise
- Click-and-use installation
- Insulation of the floor against cold and humidity

<b>Item no.</b>	<b>WL60420</b>
Model	ECOTILE-16.1043LG
Manufacturer	ECOTILE
GPSR manufacturer data	ecotile Flooring Sedgwick Road Unit 15 GB-LU4 9DT Luton www.ecotileflooring.com
Length	497 mm
Width	497 mm
Height	7 mm
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	light gray (RAL 7004)
Colour	light grey
Connection system	X-Lock
Surface texture	flat
Strength	7 mm
Type of surface	floor tile
ESD compliant	yes

## Other versions

Item no.	Strength
WL86066	5 mm
<b>WL60420</b>	<b>7 mm</b>
WL86197	10 mm