

## ESD shielding bag METAL-IN, 76 µm, 76 x 102 mm, 100 pieces



SafeGuard's shielding ESD bag is manufactured with an outer layer of conductive polyester and an inner layer of conductive polyethylene. In addition, the material thickness is 76µm. On the ESD bag the ESD and Recycle symbol, as well as type and LOT no. are printed.

- with ESD and recycle symbol, type and LOT no.
- outside: polyester conductive
- inside: polyethylene dissipative
- Metallization: aluminium-vaporized, shielding < 15 nJ
- weldable
- film thickness: 76µm +/- 10 %

Item no.	WL60823
Model	SG-ABE-ME-ABS-76MI
Manufacturer	SAFEGUARD
Manufacturer article no.	SG-ABE-ME-ABS-76MI-102X76
GPSR manufacturer data	Weidinger GmbH

Products for the electronic industry



Hertha-Sponer-Str. 1a  
DE-82216 Gernlinden

Width	76 mm
Height	102 mm
Sales unit	1 PU
Content unit	100 piece
Colour	transparent
Colour	metalised
Film thickness	76µm +/- 10 %
Zip closure	no
Packaging properties	shielding
Resealable	no
ESD certification according to IEC 61340-5-1:2016	yes
ESD compliant	yes

## Other versions

Item no.	Height x Width
<b>WL60823</b>	<b>102 mm x 76 mm</b>
WL24124	102 mm x 102 mm
WL60824	127 mm x 76 mm
WL60825	152 mm x 102 mm
WL60827	203 mm x 127 mm
WL60828	203 mm x 152 mm
WL60829	254 mm x 152 mm
WL60831	305 mm x 203 mm
WL60832	305 mm x 254 mm
WL60833	356 mm x 254 mm
WL60837	356 mm x 356 mm
WL24136	381 mm x 279 mm
WL60836	406 mm x 305 mm
WL60838	457 mm x 356 mm
WL60839	457 mm x 381 mm
WL87127	508 mm x 660 mm
WL60834	610 mm x 254 mm

Products for the electronic industry



WL60840	610 mm x 406 mm
WL60841	610 mm x 457 mm
WL60826	660 mm x 102 mm
WL60830	660 mm x 152 mm
WL60835	660 mm x 254 mm
WL60842	660 mm x 508 mm

