

ESD shielding bag METAL-IN, 76 μm , 406 x 610 mm, 100 pieces



The SafeGuard ESD bag offers optimum protection for electronic components. Made from dissipative polyester on the outside and polyethylene on the inside, it ensures safe storage. The metallization is aluminium-coated, with a shielding of less than 15 nJ. Measuring 406 x 610 mm and with a film thickness of 76 μm +/- 10 %, it is ideal for use in electronics manufacturing. Each bag is marked with the ESD and recycle symbol as well as type and LOT number and can be heat-sealed. One pack contains 100 pieces in a metallized color. The SafeGuard ESD bag meets all the requirements for shielding packaging and is ESD-compliant. Protect your sensitive components reliably with this high-quality product.

- with ESD and recycle symbol, type and LOT no.
- outside: polyester conductive
- inside: polyethylene dissipative
- Metallization: aluminium-vaporized, shielding < 15 nJ
- weldable
- film thickness: 76 μm +/- 10 %

Item no.	WL60840
Model	SG-ABE-ME-ABS-76MI
Manufacturer	SAFEGUARD
Manufacturer article no.	SG-ABE-ME-ABS-76MI-610X406
GPSR manufacturer data	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
Width	406 mm
Height	610 mm
Sales unit	1 PU
Content unit	100 piece
Colour	metalised, transparent
Incl. battery	no
Film thickness	76µm +/- 10 %
Zip closure	no
Packaging properties	shielding
Resealable	no
ESD certification according to IEC 61340-5-1:2016	yes
ESD compliant	yes

Other versions

Item no.	Height x Width
WL60823	102 mm x 76 mm
WL24124	102 mm x 102 mm
WL60824	127 mm x 76 mm
WL60825	152 mm x 102 mm
WL60827	203 mm x 127 mm
WL60828	203 mm x 152 mm
WL60829	254 mm x 152 mm
WL60831	305 mm x 203 mm
WL60832	305 mm x 254 mm
WL24137	305 mm x 457 mm
WL60833	356 mm x 254 mm
WL60837	356 mm x 356 mm

WL24136	381 mm x 279 mm
WL60836	406 mm x 305 mm
WL60838	457 mm x 356 mm
WL60839	457 mm x 381 mm
WL87127	508 mm x 660 mm
WL60834	610 mm x 254 mm
WL60840	610 mm x 406 mm
WL60841	610 mm x 457 mm
WL60826	660 mm x 102 mm
WL60830	660 mm x 152 mm
WL60835	660 mm x 254 mm
WL60842	660 mm x 508 mm

