ESD/EMI shielding bag DRY-PACK 90 µm, 254 x 508 mm, 100 pieces



The ESD/EMI shielding bag from SafeGuard can be sealed and vacuumed and, thanks to its multi-layer processing, protects the sensitive electronic components from moisture and has a defined water vapour permeability. The ESD bag is standardly printed with type designation, ESD warning symbol, recycle symbol and lot number.

- Shielding bag with moisture protection and defined water vapor permeability
- Protection against electrostatic discharge and fields
- Complies with MIL-PRF81705D Type 1 Class EIA-583
- Electrostatic shielding < 10 nJ
- Weldable, vacuum sealable
- Standard imprint: ESD/EMI marking, humidity symbol, type designation, recycle symbol, LOT no.
- Typical surface resistance Rpp = $1x10^{11}$ Ohm
- Discharge time 1000V - 100V = <0.02s
- MVTR = ≤0.0003g/100in^2/24h

Item no.	**WL60861**

Model	SG-BE-SI-VAK-90DP
Manufacturer	SAFEGUARD
Manufacturer article no.	SG-BE-SI-VAK-90DP-508X254
GPSR manufacturer data	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden
Width	254 mm
Height	508 mm
Sales unit	1 PU
Content unit	100 piece
Manufacturer colour information	silver
Colour	silver
Typical leakage resistance	$1x10^{11}$ Ohm
Film thickness	90 µm
Zip closure	no
Packaging properties	Vacuum packaging
Resealable	no
ESD certification according to IEC 61340-5-1	yes
ESD compliant	yes

Other versions

Item no.	Height x Width
WL60861	**508 mm x 254 mm**
WL60862	762 mm x 254 mm