


PVC tile X-Lock, grey, smooth, 500x500x7 mm, 4 pieces



Important: Please note the installation instructions for ecotile floor tiles. These instructions are available under "Documents" > "Download technical data sheet".

- Manufactured in UK under ISO9001 standards
- Made from REACH compliant PVC
- 497mm x 497mm x 7mm
- EN 1081, EN 1815 & EN6356
- Surface resistance of the tiles is between 3.0×10^4 Ohm/m² and 3×10^6 Ohm
- Contact resistance is between 3.6×10^5 Ohm and 9.5×10^5 Ohm
- Fire retardant - class Bfl s1
- Slip-resistant
- Chemical-resistant
- Reduces dust and noise
- Click-and-use installation
- Insulation of the floor against cold and humidity

Item no.	WL61060
Manufacturer	ECOTILE
Manufacturer article no.	X500/7/221
GPSR manufacturer data	ecotile Flooring Sedgwick Road Unit 15 GB-LU4 9DT Luton www.ecotileflooring.com
Length	500 mm
Width	497 mm
Height	7 mm
Sales unit	1 PU
Content unit	4 piece
Manufacturer colour information	grey (RAL 7015)
Colour	grey
Connection system	X-Lock
Surface texture	flat
Strength	7 mm
Type of surface	floor tile
ESD compliant	no

Other versions

Item no.	Strength
WL61060	7 mm
WL84828	10 mm