

L-BOXX® "Electric", 63 pieces

KNIPEX L-BOXX® Elektro robust box made of impact and shock-resistant ABS plastic. Equipped with 14 KNIPEX tools, a total of 63 brand-name tools, some of them VDE-tested according to DIN EN 60900. max. load: 25 kg. Max. load: 25 kg. Splash-proof. Several boxes can be reliably connected to each other. Flexible interior partitioning. Carrying handle can be recessed in a recess in the lid to save space. Ergonomically shaped handles and additional side grips for flexible and comfortable handling. With two-part tool board made of dirt-repellent PP hollow chamber panels. Tool boards are connected by Velcro. Lid section with 10 pockets and 10 elastic loops. Top bottom part with 7 pockets and tab for hanging up the tool board; also serves to lift and set up the KNIPEX L-BOXX®. Bottom section with 7 pockets and 7 elastic loops. Dimensions, outside (W x H x D): 442 x 357 x 151 mm Dimensions, inside (W x H x D): 375 x 107 x 311 mm. - Dimension width, outside (inside): 442mm 375mm - Dimension height, outside (inside): 151mm 107mm - Dimension depth, outside (inside): 442mm 311mm Scope of delivery: 1 x 12 42 195 KNIPEX MultiStrip 10 Automatic Wire Stripper (0.03 - 10.0 mm²), 1 x 00 11 01 KNIPEX TwinKey® for common cabinets and barrier systems (10 profiles. 2 crosses. 1 key.), 1 x 86 03 180 KNIPEX Pliers Wrench Pliers and wrench in one tool, 1 x 86 03 180 KNIPEX Pliers Wrench Pliers and wrench in one tool, 1 x 98 52 KNIPEX Cable Knife, 1 x 97 53 04 KNIPEX Self-Adjusting Crimping Pliers for wire end ferrules with side entry (0,08 - 10 + 16 mm²), 1 x 08 26 145 KNIPEX Pointed Combination Pliers (extra handy), 1 x 87 01 180 KNIPEX Cobra® Hightech Water Pump Pliers, 1 x 98 25 01 SL KNIPEX Screwdriver (Slim) for cross-slotted head screws Pozidriv® (PZ 1), 1 x 98 20 35 SL KNIPEX screwdriver (Slim) for slotted screws (3.5 mm), 1 x 13 86 200 KNIPEX electrical installation pliers (Ø 15 mm / 50 mm²), 1 x 16 95 01 SB KNIPEX ErgoStrip® universal stripping tool (Ø 8.0 - 13.0 mm), 1 x 70 06 160 KNIPEX side cutters, 1 x 74 06 200 KNIPEX Power Side Cutters (Optimal for all types of wire), 1 x 26 26 200 KNIPEX Flat Round Nose Pliers with cutting edge (Stork's Nose Pliers) (For narrow working areas), 1 x 5003484001 Wera VDE Interchangeable Blade Set, 16 pieces, Slim, 1 x 004018 Wera Zyklop Metal Snap Set 8100 SA 8 28-piece (1/4"), 1 x 003760 Wera Joker double open end wrench (10 x 13 mm), 1 x 0030312-0300 Picard locksmith's hammer (300 g), 1 x 101-0300 Picard locksmith's hammer (300 g), 1 x 361 252 1 Rennsteig electrician's chisel (250 x 10 mm), 1 x L240 00055 Stabila folding rule Stabila series 400 (430 mm), 1 x 16135 Stabila spirit level type 70 Electric (430 mm), 1 x 18115 Stabila mini spirit level Pocket Electric (68 mm),

- Splash-proof
- Several boxes can be reliably connected to each other
- Flexible interior division
- Carrying handle can be sunk into a recess in the lid to save space
- Ergonomically shaped handles and additional side grips for flexible and comfortable

handling

- With two-part tool board made of dirt-repellent PP hollow chamber panels
- Tool boards are connected with each other via velcro
- Lid part with 10 pockets and 10 elastic loops
- Top bottom part with 7 pockets and tab for hanging up the tool board
- Also serves to lift and set up the KNIPEX L-BOXX®.
- Bottom part with 7 pockets and 7 elastic loops
- Dimensions, outside (W x H x D): 442 x 357 x 151 mm Dimensions, inside (W x H x D): 375 x 107 x 311 mm

Article no.	WL61254
Model	00 21 19 LB E
Manufacturer	KNIPEX
Manufacturer article no.	00 21 19 LB E
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	440 mm
Width	360 mm
Height	151 mm
Length with packaging	449 mm
Width with packaging	360 mm
Height with packaging	190 mm
Volume with packaging	30.712 dm ³
Scope of delivery	1x 00 11 01 1x 86 03 180 1x 98 52 1x 98 25 01 SL 1x 98 20 35 SL 1x 12 42 195 1x 13 86 200 1x 16 95 01 SB 1x 70 06 160 1x 74 06 200 1x 97 53 04 1x 26 26 200 1x 08 26 145 1x 87 01 180
Sales unit	1 piece
Content unit	1 piece

Product series	L-BOXX®
RoHS compliant	no
VDE	no
ESD compliant	no