Power combination pliers, black atramentized, 225 mm



35 % force saving compared to conventional combination pliers. With cutting edges (hardness approx. 63 HRC) for heavy-duty use. Easier working due to optimised transmission. Easier cutting, powerful gripping, bending and pulling. Long cutting edges for thicker cables. With gripping zones for flat and round material for versatile use. Cutting edges additionally induction hardened, cutting edge hardness approx. 63 HRC. - Cutting values hard wire (diameter): Ø 3,0mm - Cutting values piano wire (diameter): Ø 2,5mm - Cutting values Cu-cable, stranded: Ø 14,0mm - Cutting values Cu-cable, stranded: 25,0mm^2

- Easier working due to optimised transmission ratio
- Easier cutting, powerful gripping, bending and pulling
- Long cutting edges for thicker cables
- With gripping zones for flat and round material for versatile use
- Cutting edges additionally induction hardened, cutting edge hardness approx. 63 HRC

Item no.	**WL61275**
Model	02 02 225
Manufacturer	KNIPEX
Manufacturer article no.	02 02 225
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	235 mm
Width	55 mm
Height	25 mm
Length with packaging	323 mm

Width with packaging	124 mm
Height with packaging	56 mm
Volume with packaging	2.283 dm^3
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Standards	DIN ISO 5746
RoHS compliant	no
Surface	black atramentised
VDE	no
ESD compliant	no
Fastening for fall protection	nein
Tool length	225 mm
Description Head	polished
Grip (expression)	With multi-component handles
Cutting value copper cable, stranded	25 mm^2
Cutting value copper cable, stranded (diameter)	14 mm
Cutting value wire diameter (hard)	3 mm
Type of pliers	combination pliers

Other versions

Item no.	Tool length	Fastening for fall protection
WL61273	180 mm	nein
WL30498	200 mm	nein
WL61275	**225 mm**	**nein**