

## Combination pliers, black afromentized, 160 mm



With gripping zones for flat and round material for versatile use. With cutting edges for soft and hard wire. Long cutting edges for thicker cables. Cutting edges additionally induction hardened, cutting edge hardness approx. 60 HRC. - Cutting values medium hard wire (diameter): Ø 3,1mm - Cutting values hard wire (diameter): Ø 2,0mm - Cutting values Cu-cable, stranded: Ø 10,0mm - Cutting values Cu-cable, stranded: 16,0mm<sup>2</sup>

- With gripping zones for flat and round material for versatile use
- With cutting edges for soft and hard wire
- Long cutting edges for thicker cables
- Cutting edges additionally induction hardened, cutting edge hardness approx. 60 HRC

<b>Item no.</b>	<b>WL61284</b>
Model	03 01 160
Manufacturer	KNIPEX
Manufacturer article no.	03 01 160
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	160 mm
Width	48 mm
Height	13 mm
Length with packaging	206 mm
Width with packaging	86 mm
Height with packaging	37 mm

Products for the electronic industry



Volume with packaging	0.655 dm <sup>3</sup>
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN ISO 5746
RoHS compliant	no
Surface	black amentised
VDE	no
ESD compliant	no
Tool length	160 mm
Description Head	polished
Grip (expression)	Covered with plastic
Cutting value copper cable, stranded	16 mm <sup>2</sup>
Cutting value copper cable, stranded (diameter)	10 mm
Cutting value wire diameter (hard)	2 mm
Cutting value wire diameter (medium)	3.1 mm
Type of pliers	combination pliers

## Other versions

Item no.	Tool length
WL61283	140 mm
<b>WL61284</b>	<b>160 mm</b>
WL61285	180 mm
WL61286	200 mm
WL61287	250 mm